


E2LK508V-XXP

PCB Terminal Blocks > PCB Terminal Blocks

Date:2025-12-03Version:V1





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

Pitch: 5.08mm, 300V, 13.5A

General information

Short description	PCB Terminal Blocks, Screw Connection
Category	PCB Terminal Blocks
Pitch (mm)	5.08
Color	Green (default)
Connection method	Screw Connection
Type of locking	Without
Length (mm)	5.08*(P-1)+5.08
Width (mm)	8.6
Height (mm)	19.1
Pin demensions (Thickness x Width)(mm)	0.5x1.0
PCB hole diameter (mm)	1.3
Number of positions	02P~24P
Level	Single level

Material information

Insulation material	PA
---------------------	----




Insulation material group	I
Flame retardant rating , compliant with UL94	VO
Insulation resistance	□500MΩ at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED
Connection data-IEC	
Rated voltage (V)	320
Rated current (A)	13.5
Rated voltage (II/2)(V)	630
Rated voltage (III/2) (V)	320
Rated voltage (III/3)(V)	250
Rated impulse voltage (II/2)(KV)	4
Rated impulse voltage (III/2)(KV)	4
Rated impulse voltage (III/3)(KV)	4
Conductor cross section solid. min (mm²)	0.5
Conductor cross section solid.max (mm²)	1.5
Conductor cross section stranded. min (mm²)	0.5
Conductor cross section stranded. max (mm²)	1.5
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.5
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	0.75
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.5
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	0.75
2 conductors with same cross section, solid, min (mm²)	0.5
2 conductors with same cross section, solid, max (mm²)	0.75
2 conductors with same cross section, stranded, min (mm²)	0.5
2 conductors with same cross section, stranded, max (mm²)	0.75
2 conductors with same cross section flexible, with min ferrule without plastic sleeve (mm²)	0.5
2 conductors with same cross section flexible, with max ferrule without plastic sleeve (mm²)	0.5
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	0.5

2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)		
Screw thread	M2.5	
Slotted screwdriver size (Blade thickness x Width)(mm)	0.6x3.5	
Recommend tightening torque. min (N.m)	0.4	
Recommend tightening torque. max (N.m)	0.5	
Stripping Length (mm)	6~7	
Connection data-UL		
Rated voltage (UL/CUL Group B)(V)	300	
Rated current (UL/CUL Group B)(A)	13.5	
Rated voltage (UL/CUL Group D)(V)	300	
Rated current (UL/CUL Group D)(A)	10	
Min. solid wire connection (AWG) acc. to UL/CUL	30	
Max. solid wire connection AWG acc. to UL/CUL	14	
Min. stranded wire connection AWG acc. to UL/CUL	30	
Max. stranded wire connection AWG acc. to UL/CUL	14	
Environment & Safety	14	
	YES	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C)		
Environment & Safety Finger protection (YES or NO)	YES	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C)	YES 120	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C)	YES 120	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized	YES 120 -40	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG)	YES 120 -40	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG) Rated voltage (Group B)(V)	YES 120 -40 30~14 300	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG) Rated voltage (Group B)(V) Rated current (Group B)(A)	YES 120 -40 30~14 300 13.5	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG) Rated voltage (Group B)(V) Rated current (Group B)(A) Wire Range (Group D)(AWG)	YES 120 -40 30~14 300 13.5 30~14	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG) Rated voltage (Group B)(V) Rated current (Group B)(A) Wire Range (Group D)(AWG) Rated voltage (Group D)(V)	YES 120 -40 30~14 300 13.5 30~14 300	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG) Rated voltage (Group B)(V) Rated current (Group B)(A) Wire Range (Group D)(AWG) Rated voltage (Group D)(V) Rated current (Group D)(V)	YES 120 -40 30~14 300 13.5 30~14 300	
Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) JL Recognized Wire Range (Group B)(AWG) Rated voltage (Group B)(V) Rated current (Group B)(A) Wire Range (Group D)(AWG) Rated voltage (Group D)(V) Rated current (Group D)(V)	YES 120 -40 30~14 300 13.5 30~14 300 10	



Wire Ranget (Group D)(AWG)	30~14
Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	10

Drawings



Approvals





