




# TKE02

PCB Terminal Blocks > Transformer Terminal Blocks

Date:2025-10-30Version:1.2







The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

### **Product Description**

M3, 600V, 15A

#### General information

Short description	Transformer terminal blocks, Screw connection
Color	Gray (default)
Connection method	Screw connection
Type of locking	Without

### Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	VO
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED

#### Connection data-IEC

Rated voltage (V)	800
Rated current (A)	17.5
Rated voltage (III/3)(V)	800

Rated impulse voltage (II/2)(KV)	5
Rated impulse voltage (III/2)(KV)	5
Rated impulse voltage (III/3)(KV)	5
Conductor cross section solid. min (mm²)	0.5
Conductor cross section solid.max (mm²)	1.5
Conductor cross section stranded. min (mm²)	0.5
Conductor cross section stranded. max (mm²)	1.5
Screw thread	M3
Slotted screwdriver size (Blade thickness x Width)(mm)	1x5.5
Philips screwdriver size	PH2
Rated torque (N.m)	0.5~0.6
Stripping Length (mm)	9~10
Connection data-UL  Pated voltage (UL/CUL Group B)(V)	600
Rated voltage (UL/CUL Group B)(V)	600
Rated current (UL/CUL Group B)(A)	15
Rated voltage (UL/CUL Group C)(V)	600
Rated current (UL/CUL Group C)(A)	15
Rated voltage (UL/CUL Group D)(V)	600
Rated current (UL/CUL Group D)(A)	5
Min. solid wire connection (AWG) acc. to UL/CUL	20
Max. solid wire connection AWG acc. to UL/CUL	16
Min. stranded wire connection AWG acc. to UL/CUL	20
Max. stranded wire connection AWG acc. to UL/CUL	16
Environment & Safety	
Back of the hand protection (YES or NO)	YES
Finger protection (YES or NO)	YES
Operating temperature. max (°C)	115
Operating temperature. min (°C)	-40
JL Recognized	
Wire Range (Group B)(AWG)	16~20
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	15




Wire Range (Group C)(AWG)	16~20
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	15
Wire Range (Group D)(AWG)	16~20
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	5

### **CUL** Recognized

Wire Range (Group B)(AWG)	16~20
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	15
Wire Range (Group C)(AWG)	16~20
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	15
Wire Ranget (Group D)(AWG)	16~20
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	5

# Drawings



## Approvals







