
# 0225-47XX

PCB Terminal Blocks > PCB Connector-Socket

Date:2026-11-17Version:V1






The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.
The final product is made according to engineering drawing.

## Product Description

Pitch : 5.08 mm, 300V, 12A

## General information

| | |
|---|---|
| Short description | PCB Connector–Socket, Wave soldering |
| Category | PCB Connector–Socket |
| Pitch (mm) | 5.08 |
| Color | Black (default) |
| Type of locking | With threaded flange |
| Soldering method | Wave soldering |
| Length (mm) | 5.08*(P/2-1)+14.54 |
| Width (mm) | 9.5 |
| Height (mm) | 16 |
| Pin demensions (Thickness x Width)(mm) | 0.6x0.8 |
| PCB hole diameter (mm) | 1.2 |
| Number of positions | 04P~40P |
| Level | Double level |

## Material information

| | |
|---|---|
| Insulation material | PBT |


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED

| | |
|---|---|
| Insulation material group | IIIa |
| Flame retardant rating , compliant with UL94 | V0 |
| Insulation resistance | □1000MΩ at DC 500V |
| Conductor material | COPPER ALLOY |
| Plating of conductor surface | Tin PLATED |

## Connection data-IEC

| | |
|---|---|
| Rated voltage (V) | 320 |
| Rated current (A) | 14 |
| Rated voltage (II/2)(V) | 320 |
| Rated voltage (III/2) (V) | 320 |
| Rated voltage (III/3)(V) | 200 |
| Rated impulse voltage (II/2)(KV) | 4 |
| Rated impulse voltage (III/2)(KV) | 4 |
| Rated impulse voltage (III/3)(KV) | 4 |
| Tightening torque with flange. max (N.m) | 0.1 |

## Connection data-UL

| | |
|---|---|
| Rated voltage (UL/CUL Group B)(V) | 300 |
| Rated current (UL/CUL Group B)(A) | 12 |
| Rated voltage (UL/CUL Group D)(V) | 300 |
| Rated current (UL/CUL Group D)(A) | 10 |

## Environment & Safety

| | |
|---|---|
| Finger protection (YES or NO) | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## UL Recognized


| | |
|---|---|
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 12 |
| Rated voltage (Group D)(V) | 300 |
| Rated current (Group D)(A) | 10 |


## CUL Recognized


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED

| | |
|---|---|
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 12 |
| Rated voltage (Group D)(V) | 300 |
| Rated current (Group D)(A) | 10 |

## Drawings




## Approvals


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED