


DP4N

DIN Rail Terminal Blocks > Push-in Design

Date:2025-11-04Version:1.1





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

600V, 30A, Beige (default)

General information

Short description	Single level Feed-Through Terminal Block, Push-in Design
Category	Single level Feed Through Terminal Block
Color	Beige (default)
Connection method	Push-in Design
Type of locking	Rail Mounting
Length (mm)	57
Width (mm)	6.1
Height (mm)	35
Number of positions	<u>≥</u> 1P
Level	Single level
Connection points	2

Material information

Insulation material	PA
Insulation material group	I




Flame retardant rating , compliant with UL94	V0
Insulation resistance	≧500MΩ at DC 500V
Connection data-IEC	
Rated voltage (V)	800
Rated current (A)	32
Rated voltage (III/3)(V)	800
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm²)	0.2
Conductor cross section solid.max (mm²)	6
Conductor cross section stranded. min (mm²)	0.2
Conductor cross section stranded. max (mm²)	4
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.25
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	4
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.25
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	4
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	0.5
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)	1
Slotted screwdriver size (Blade thickness x Width)(mm)	0.8x4.0
Stripping Length (mm)	12
Mounting rail	TS-35 \ TS-35/15
End cover plate required	YES
Grounding connections	NO
Connection data-UL	
Rated voltage (UL/CUL Group B)(V)	600
Rated current (UL/CUL Group B)(A)	30
Rated voltage (UL/CUL Group C)(V)	600
Rated current (UL/CUL Group C)(A)	30
Min. solid wire connection (AWG) acc. to UL/CUL	24
Max. solid wire connection AWG acc. to UL/CUL	10
Min. stranded wire connection AWG acc. to UL/CUL	24



Max. stranded wire connection AWG acc. to UL/CUL	10	
Environment & Safety		
Back of the hand protection (YES or NO)	YES	
Finger protection (YES or NO)	YES	
Operating temperature. max (°C)	120	
Operating temperature. min (°C)	-40	
UL Recognized		
Wire Range (Group B)(AWG)	24~10	
Rated voltage (Group B)(V)	600	
Rated current (Group B)(A)	30	
Wire Range (Group C)(AWG)	24~10	
Rated voltage (Group C)(V)	600	
Rated current (Group C)(A)	30	
CUL Recognized		
Wire Range (Group B)(AWG)	24~10	
Rated voltage (Group B)(V)	600	
Rated current (Group B)(A)	30	
Wire Range (Group C)(AWG)	24~10	
Rated voltage (Group C)(V)	600	
Rated current (Group C)(A)	30	

Drawings





Approvals







