
# 0138-61XXL

PCB Terminal Blocks > PCB Terminal Blocks

Date:2026-10-31






The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design. The final product is made according to engineering drawing.

## Product Description

Pitch : 5.08 mm, 300V, 12A

## General information

| | |
|---|---|
| Short description | PCB Terminal Blocks, Push-in Design |
| Category | PCB Terminal Blocks |
| Pitch (mm) | 5.08 |
| Color | Black (default) |
| Connection method | Push in Design |
| Type of locking | Without |
| Soldering method | Reflow Soldering (Temperature condition according to standard IPC/JEDEC J-STD-020E) |
| Length (mm) | 5.08*(P-1)+4.2 |
| Width (mm) | 14 |
| Height (mm) | 8.5 |
| Pin demensions (Thickness x Width)(mm) | 0.35x0.7 |
| PCB hole diameter (mm) | 1.0~1.1 |
| Number of positions | 02P~24P |
| Level | Single level |
| Connection points | 1 |


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED

## Material information

| | |
|---|---|
| Insulation material | HIGH-TEMPERATURE PLASTICS |
| Insulation material group | IIIa |
| Flame retardant rating , compliant with UL94 | V0 |
| Insulation resistance | □500MΩ at DC 500V |
| Conductor material | COPPER ALLOY |
| Plating of conductor surface | Tin PLATED |
| MSL | 1 |

## Connection data-IEC

| | |
|---|---|
| Rated voltage (V) | 320 |
| Rated current (A) | 17.5 |
| Rated voltage (II/2)(V) | 500 |
| Rated voltage (III/2) (V) | 320 |
| Rated voltage (III/3)(V) | 250 |
| Rated impulse voltage (II/2)(KV) | 4 |
| Rated impulse voltage (III/2)(KV) | 4 |
| Rated impulse voltage (III/3)(KV) | 4 |
| Conductor cross section solid. min (mm²) | 0.14 |
| Conductor cross section solid.max (mm²) | 1.5 |
| Conductor cross section stranded. min (mm²) | 0.14 |
| Conductor cross section stranded. max (mm²) | 1.5 |
| Conductor cross section flexible, with min ferrule without plastic sleeve (mm²) | 0.25 |
| Conductor cross section flexible, with max ferrule without plastic sleeve (mm²) | 1.5 |
| Conductor cross section flexible, with min ferrule with plastic sleeve (mm²) | 0.25 |
| Conductor cross section flexible, with max ferrule with plastic sleeve (mm²) | 1.5 |
| Slotted screwdriver size (Blade thickness x Width)(mm) | 0.4x2.5 |
| Stripping Length (mm) | 8~9 |

## Connection data-UL

| | |
|---|---|
| Rated voltage (UL/CUL Group B)(V) | 300 |
| Rated current (UL/CUL Group B)(A) | 12 |


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED

| | |
|---|---|
| Rated voltage (UL/CUL Group D)(V) | 300 |
| Rated current (UL/CUL Group D)(A) | 12 |
| Min. solid wire connection (AWG) acc. to UL/CUL | 28 |
| Max. solid wire connection AWG acc. to UL/CUL | 14 |
| Min. stranded wire connection AWG acc. to UL/CUL | 28 |
| Max. stranded wire connection AWG acc. to UL/CUL | 14 |

## Environment & Safety

| | |
|---|---|
| Finger protection (YES or NO) | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## UL Recognized


| | |
|---|---|
| Wire Range (Group B)(AWG) | 28~14 |
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 12 |
| Wire Range (Group D)(AWG) | 28~14 |
| Rated voltage (Group D)(V) | 300 |
| Rated current (Group D)(A) | 12 |


## CUL Recognized

| | |
|---|---|
| Wire Range (Group B)(AWG) | 28~14 |
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 12 |
| Wire Ranget (Group D)(AWG) | 28~14 |
| Rated voltage (Group D)(V) | 300 |
| Rated current (Group D)(A) | 12 |

## Drawings


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED




## Approvals


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED