
# ECH116HVS-XXP

PCB Terminal Blocks > PCB Connector-Socket

Date:2026-11-17






The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.
The final product is made according to engineering drawing.

## Product Description

Pitch : 10.16 mm, 600V, 51A

## General information

| | |
|---|---|
| Short description | PCB Connector–Socket, Wave soldering |
| Category | PCB Connector–Socket |
| Pitch (mm) | 10.16 |
| Color | Green (default) |
| Type of locking | Without |
| Soldering method | Wave Soldering |
| Length (mm) | 10.16*(P-1)+10.16 |
| Width (mm) | 13.7 |
| Height (mm) | 32 |
| Pin demensions (Thickness x Width)(mm) | 1.0x3.6 |
| PCB hole diameter (mm) | 1.5x4.7 |
| Number of positions | 02~10P |
| Level | Single level |
| Connection points | 1 |

## Material information


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED

| | |
|---|---|
| Insulation material | PA |
| Insulation material group | I |
| Flame retardant rating , compliant with UL94 | V0 |
| Insulation resistance | □500MΩ at DC 500V |
| Conductor material | COPPER ALLOY |
| Plating of conductor surface | Ag PLATED |

## Connection data-IEC

| | |
|---|---|
| Rated voltage (V) | 1000 |
| Rated current (A) | 76 |
| Rated voltage (II/2)(V) | 1000 |
| Rated voltage (III/2) (V) | 1000 |
| Rated voltage (III/3)(V) | 1000 |
| Rated impulse voltage (II/2)(KV) | 8 |
| Rated impulse voltage (III/2)(KV) | 8 |
| Rated impulse voltage (III/3)(KV) | 8 |

## Connection data-UL

| | |
|---|---|
| Rated voltage (UL/CUL Group B)(V) | 600 |
| Rated current (UL/CUL Group B)(A) | 51 |
| Rated voltage (UL/CUL Group C)(V) | 600 |
| Rated current (UL/CUL Group C)(A) | 51 |
| Rated voltage (UL/CUL Group D)(V) | 600 |
| Rated current (UL/CUL Group D)(A) | 5 |

## Environment & Safety

| | |
|---|---|
| Finger protection (YES or NO) | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## UL Recognized

| | |
|---|---|
| Rated voltage (Group B)(V) | 600 |
| Rated current (Group B)(A) | 51 |
| Rated voltage (Group C)(V) | 600 |
| Rated current (Group C)(A) | 51 |



© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED


| | |
|---|---|
| Rated voltage (Group D)(V) | 600 |
| Rated current (Group D)(A) | 5 |

## CUL Recognized

| | |
|---|---|
| Rated voltage (Group B)(V) | 600 |
| Rated current (Group B)(A) | 51 |
| Rated voltage (Group C)(V) | 600 |
| Rated current (Group C)(A) | 51 |
| Rated voltage (Group D)(V) | 600 |
| Rated current (Group D)(A) | 5 |

## Drawings




## Approvals


© DINKLE ENTERPRISE CO ,LTD. ALL RIGHT RESERVED