


# ECH381RR-XXPLWR

PCB Terminal Blocks > In tape-on-reel packing

Date:2025-11-03Version:V1





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

### **Product Description**

Pitch: 3.81 mm, 300V, 8A

#### General information

Short description	PCB Connector – Socket, Reflow soldering
Category	PCB Connector – Socket
Pitch (mm)	3.81
Color	Black (default)
Type of locking	Without
Soldering method	Reflow Soldering (Temperature condition according to standard IPC/JEDEC J-STD-020E)
Length (mm)	3.81*(P-1)+4.8
Width (mm)	9.2
Height (mm)	7.2
Pin demensions (Thickness x Width)(mm)	0.8x0.8
PCB hole diameter (mm)	1.4
Number of positions	02P~24P
Level	Single level




#### Material information

	HIGH-TEMPERATURE PLASTICS
Insulation material group	IIIa
Flame retardant rating , compliant with UL94	VO
Insulation resistance	□500MΩ at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED
MSL	1
Connection data-IEC	
Rated voltage (V)	320
Rated current (A)	14
Rated voltage (II/2)(V)	320
Rated voltage (III/2) (V)	160
Rated voltage (III/3)(V)	160
Rated impulse voltage (II/2)(KV)	2.5
Rated impulse voltage (III/2)(KV)	2.5
Rated impulse voltage (III/3)(KV)	2.5
Connection data-UL	
Rated voltage (UL/CUL Group B)(V)	300
· · · · · · · · · · · · · · · · · · ·	8
· · · · · · · · · · · · · · · · · · ·	300
Rated current (UL/CUL Group B)(A)	
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)	300
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A) Environment & Safety	300
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)	300 8
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)  Environment & Safety  Finger protection (YES or NO)	300 8 YES
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)  Environment & Safety  Finger protection (YES or NO)  Operating temperature. max (°C)  Operating temperature. min (°C)	300 8 YES 120
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)  Environment & Safety  Finger protection (YES or NO)  Operating temperature. max (°C)  Operating temperature. min (°C)	300 8 YES 120
Rated current (UL/CUL Group B)(A) Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)  Environment & Safety  Finger protection (YES or NO)  Operating temperature. max (°C)  Operating temperature. min (°C)  UL Recognized	300 8 YES 120 -40



Rated current (Group D)(A)	8
CUL Recognized	
Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	8
Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	8

## Drawings



## Approvals





