


# DPES2.5QK04

DIN Rail Terminal Blocks > Push-in Design

Date:2025-10-30





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

#### **Product Description**

600V, 20A, Beige (default)

#### General information

Short description	Plug-in Connection Terminal Block, Push-in Design
Category	Plug-in Connection Terminal Block
Pitch (mm)	5.08
Color	Beige (default)
Connection method	Push-in Design
Type of locking	Rail Mounting
Length (mm)	83.3
Width (mm)	60
Height (mm)	84
Number of positions	16
Level	Single level
Connection points	32

#### Material information

Insulation material	PA
Insulation material group	I




Flame retardant rating , compliant with UL94	VO
Insulation resistance	≥500MΩ at DC 500V
Connection data-IEC	
Rated voltage (V)	800
Rated current (A)	24
Rated voltage (III/3)(V)	800
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm²)	0.14
Conductor cross section solid.max (mm²)	4
Conductor cross section stranded. min (mm²)	0.14
Conductor cross section stranded. max (mm²)	2.5
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.25
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	2.5
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.25
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	2.5
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	0.5
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)	0.5
Slotted screwdriver size (Blade thickness x Width)(mm)	0.6x3.5
Stripping Length (mm)	9~10
Mounting rail	TS-35
End cover plate required	YES
Grounding connections	NO
Connection data-UL	
Rated voltage (UL/CUL Group B)(V)	600
Rated current (UL/CUL Group B)(A)	20
Rated voltage (UL/CUL Group C)(V)	600
Rated current (UL/CUL Group C)(A)	20
Min. solid wire connection (AWG) acc. to UL/CUL	26
Max. solid wire connection AWG acc. to UL/CUL	12
Min. stranded wire connection AWG acc. to UL/CUL	26



Max. stranded wire connection AWG acc. to UL/CUL	12	
Environment & Safety		
Back of the hand protection (YES or NO)	YES	
Finger protection (YES or NO)	YES	
Operating temperature. max (°C)	120	
Operating temperature. min (°C)	-40	
UL Recognized		
Wire Range (Group B)(AWG)	26~12	
Rated voltage (Group B)(V)	600	
Rated current (Group B)(A)	20	
Wire Range (Group C)(AWG)	26~12	
Rated voltage (Group C)(V)	600	
Rated current (Group C)(A)	20	
CUL Recognized		
Wire Range (Group B)(AWG)	26~12	
Rated voltage (Group B)(V)	600	
Rated current (Group B)(A)	20	
Wire Range (Group C)(AWG)	26~12	
Rated voltage (Group C)(V)	600	
Rated current (Group C)(A)	20	

## Drawings





### Approvals





