


0159-33XX

PCB Terminal Blocks > PCB Connector-Socket

Date:2025-09-10





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

Pitch: 3.50mm, 300V, 8A

General information

Short description	PCB Connector – Socket, Wave soldering
Category	PCB Connector – Socket
Pitch (mm)	3.5
Color	Black (default)
Type of locking	Without
Soldering method	Wave Soldering
Length (mm)	3.50*(P/2-1)+4.3
Width (mm)	11.6
Height (mm)	13.3
Pin demensions (Thickness x Width)(mm)	0.8X0.8
PCB hole diameter (mm)	1.4
Number of positions	04P~40P
Level	Double level

Material information


Insulation material	PA
---------------------	----

Insulation material group	I
Flame retardant rating , compliant with UL94	V0
Insulation resistance	\square 500M Ω at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED
Connection data-IEC	
Rated voltage (V)	320
Rated current (A)	8
Rated voltage (II/2)(V)	320
Rated voltage (III/2) (V)	160
Rated voltage (III/3)(V)	160
Rated impulse voltage (II/2)(KV)	2.5
Rated impulse voltage (III/2)(KV)	2.5
Rated impulse voltage (III/3)(KV)	2.5
Connection data-UL	
Rated voltage (UL/CUL Group B)(V)	150
Rated current (UL/CUL Group B)(A)	8
Rated voltage (UL/CUL Group C)(V)	50
Rated current (UL/CUL Group C)(A)	8
Rated voltage (UL/CUL Group D)(V)	300
Rated current (UL/CUL Group D)(A)	8
Environment & Safety	
Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40
UL Recognized	
Rated voltage (Group B)(V)	150
Rated current (Group B)(A)	8
Rated voltage (Group C)(V)	50
Rated current (Group C)(A)	8
Rated voltage (Group D)(V)	300



Rated current (Group D)(A)	8	
CUL Recognized		
Rated voltage (Group B)(V)	150	
Rated current (Group B)(A)	8	
Rated voltage (Group C)(V)	50	
Rated current (Group C)(A)	8	
Rated voltage (Group D)(V)	300	
Rated current (Group D)(A)	8	

Drawings



Approvals





