
0177-03XX

PCB Terminal Blocks > PCB Terminal Blocks

Date:2025-12-04





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

Pitch: 10.00mm, 300V, 66A

General information

Short description	PCB Terminal Blocks, Push-in Design
Category	PCB Terminal Blocks
Pitch (mm)	10
Color	Black (default)
Connection method	Push-in Design
Type of locking	Without
Soldering method	Wave Soldering
Length (mm)	10.00*(P-1)+11.8
Width (mm)	31.3
Height (mm)	24.7
Pin demensions (Thickness x Width)(mm)	1x 1.2
PCB hole diameter (mm)	1.7
Number of positions	02P~12P
Level	Single level
Connection points	2~12



Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	VO
Insulation resistance	□500MΩ at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED

Connection data-IEC

Rated voltage (V)	320
Rated current (A)	76
Rated voltage (II/2)(V)	630
Rated voltage (III/2) (V)	320
Rated voltage (III/3)(V)	320
Rated impulse voltage (II/2)(KV)	4
Rated impulse voltage (III/2)(KV)	4
Rated impulse voltage (III/3)(KV)	4
Conductor cross section solid. min (mm²)	0.75
Conductor cross section solid.max (mm²)	16
Conductor cross section stranded. min (mm²)	0.75
Conductor cross section stranded. max (mm²)	16
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.75
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	16
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.75
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	10
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	0.75
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)	4
Slotted screwdriver size (Blade thickness x Width)(mm)	0.8x4
Stripping Length (mm)	18~20


Connection data-UL

Rated voltage (UL/CUL Group B)(A)	36060
Rated voltage (UL/CUL Group C)(V)	150
Rated current (UL/CUL Group C)(A)	66
Rated voltage (UL/CUL Group D)(V)	300
Rated current (UL/CUL Group D)(A)	10
Min. solid wire connection (AWG) acc. to UL/CUL	20
Max. solid wire connection AWG acc. to UL/CUL	4
Min. stranded wire connection AWG acc. to UL/CUL	20
Max. stranded wire connection AWG acc. to UL/CUL	4
Environment & Safety	
Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40
UL Recognized	
Wire Range (Group B)(AWG)	20~4
Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	66
Wire Range (Group C)(AWG)	20~4
Rated voltage (Group C)(V)	150
Rated current (Group C)(A)	66
Wire Range (Group D)(AWG)	20~4
Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	10
CUL Recognized	
Wire Range (Group B)(AWG)	20~4
Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	66
Wire Range (Group C)(AWG)	20~4
Rated voltage (Group C)(V)	150
Rated current (Group C)(A)	66
Wire Ranget (Group D)(AWG)	20~4



Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	10

Drawings



Approvals





