


0290-51XXM

PCB Terminal Blocks > PCB Terminal Blocks

Date:2026-08-03



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.
The final product is made according to engineering drawing.

Product Description

Pitch :15.00, 1000V, 101A

General information

Short description	PCB Terminal Blocks, Push-in Design
Category	PCB Terminal Blocks
Pitch (mm)	15.00
Color	Refer to drawing
Connection method	Push-in Design
Type of locking	With mounting flange
Soldering method	Wave soldering
Length (mm)	15.00*P+18
Width (mm)	49.8
Height (mm)	48
Pin dimensions (Thickness x Width)(mm)	1.5x1.8
PCB hole diameter (mm)	2.8
Number of positions	01~06P
Level	Single level
Connection points	1~6

Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	V0
Insulation resistance	□500MΩ at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED

Connection data-IEC

Rated voltage (V)	1000
Rated current (A)	125
Rated voltage (II/2)(V)	1000
Rated voltage (III/2) (V)	1000
Rated voltage (III/3)(V)	1000
Rated impulse voltage (II/2)(KV)	8
Rated impulse voltage (III/2)(KV)	8
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm²)	2.5
Conductor cross section solid.max (mm²)	35
Conductor cross section stranded. min (mm²)	2.5
Conductor cross section stranded. max (mm²)	25
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	2.5
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	35
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	2.5
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	35
Philips screwdriver size	1x5.5
Tightening torque with flange. max (N.m)	0.5
Stripping Length (mm)	24~26

Connection data-UL

Rated voltage (UL/CUL Group B)(V)	600
Rated current (UL/CUL Group B)(A)	101

Rated voltage (UL/CUL Group C)(V)	600
Rated current (UL/CUL Group C)(A)	101
Rated voltage (UL/CUL Group D)(V)	600
Rated current (UL/CUL Group D)(A)	5
Min. solid wire connection (AWG) acc. to UL/CUL	14
Max. solid wire connection AWG acc. to UL/CUL	2
Min. stranded wire connection AWG acc. to UL/CUL	14
Max. stranded wire connection AWG acc. to UL/CUL	2

Environment & Safety

Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40


UL Recognized

Wire Range (Group B)(AWG)	14~2
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	101
Wire Range (Group C)(AWG)	14~2
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	10
Wire Range (Group D)(AWG)	14~2
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	5

CUL Recognized

Wire Range (Group B)(AWG)	14~2
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	101
Wire Range (Group C)(AWG)	14~2
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	101
Wire Range (Group D)(AWG)	14~2
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	5

Drawings



Approvals

