


# EDH130F-XX/12.6

PCB Terminal Blocks &gt; PCB Connector-Socket

Date:2026-02-06 Version:V1



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

Pitch : 5.00 mm, 300V, 7A

## General information

Short description	PCB Connector – Socket, Wave soldering
Category	PCB Connector – Socket
Pitch (mm)	5.00
Color	Grey (default)
Type of locking	Without
Soldering method	Wave soldering
Length (mm)	5.00*(P-1)+5.0
Width (mm)	2.8
Height (mm)	12.6
Pin demensions (Thickness x Width)(mm)	1.3
PCB hole diameter (mm)	2
Number of positions	02P~20P
Level	Single level

## Material information

Insulation material	PBT
---------------------	-----

Insulation material group	IIIa
Flame retardant rating , compliant with UL94	V0
Insulation resistance	□1000MΩ at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED

### Connection data-IEC

Rated voltage (V)	320
Rated current (A)	8
Rated voltage (II/2)(V)	320
Rated voltage (III/2) (V)	320
Rated voltage (III/3)(V)	200
Rated impulse voltage (II/2)(KV)	4
Rated impulse voltage (III/2)(KV)	4
Rated impulse voltage (III/3)(KV)	4

### Connection data-UL

Rated voltage (UL/CUL Group B)(V)	300
Rated current (UL/CUL Group B)(A)	7
Rated voltage (UL/CUL Group D)(V)	300
Rated current (UL/CUL Group D)(A)	7

### Environment & Safety

Finger protection (YES or NO)	NO
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40

### UL Recognized



Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	7
Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	7

### CUL Recognized

Rated voltage (Group B)(V)	300
----------------------------	-----

Rated current (Group B)(A)	7
Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	7

## Drawings



## Approvals

