


W3K500-XXP

PCB > PCB :2025-11-05 :V1





Pitch: 5.00mm, 300V, 10A

	PCB Terminal Blocks, Spring Clamp Connection
	PCB Terminal Blocks
(mm)	5.00
	Grey (default)
	Spring Clamp Connection
	Without
(mm)	5.00*(P/3-1)+6.0
(mm)	31.2
(mm)	39
(x) (mm)	0.7×0.7
PCB (mm)	1.2
()	03P~72P
	Triple level
	I I

	PA
	I
UL 94	V0

	500M at DC 500V
	COPPER ALLOY
	Tin PLATED
-IEC	
(V)	450
(A)	24
(II/2)(V)	630
(III/2)(V)	450
(III/3)(V)	320
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4
(mm ²)	0.5
(mm ²)	2.5
(mm ²)	0.5
(mm ²)	2.5
(mm²)	0.5
(mm²)	1.5
(mm ²)	0.5
(mm ²)	1.5
$\frac{2}{(\text{mm}^2)}$, ,	0.5
2 (mm²)	1
(Blade thickness x Width)(mm)	0.6x3.5
	6~7
-UL	
(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	10
(UL/CUL Group C)(V)	150
(UL/CUL Group C)(A)	10

(UL/CUL Group D)(V)		300
(UL/CUL Group D)(A)		10
UL/CUL	AWG	28
UL/CUL	AWG	12
UL/CUL	AWG	28
UL/CUL	AWG	12
&		
가 (YES or NO)		YES
		120
		-40
UL		
(Group B)(AWG)		28~12
(Group B)(V)		300
(Group B)(A)		10
(Group C)(AWG)		28~12
(Group C)(V)		150
(Group C)(A)		10
(Group D)(AWG)		28~12
(Group D)(V)		150
(Group D)(A)		10
CUL		
(Group B)(AWG))	28~12
(Group B)(V)		300
(Group B)(A)		10
(Group C)(AWG))	28~12
(Group C)(V)		150
(Group C)(A)		10
(Group D)(AWG)		28~12
(Group D)(V)		150
(Group D)(A)		10

