


EC880V-XXP

PCB > PCB -

:2026-02-10 :1.1



Pitch : 8.80 mm, 600V, 30A

	PCB Connector Plug, Screw Connection
	PCB Connector Plug
(mm)	8.80
	Green(default)
	Screw Connection
	Without
(mm)	8.80x(P-1)+8.50
(mm)	32.3
(mm)	27
()	02~12
	Single level

UL 94	PA I VO
	Copper Alloy Tinned

-IEC

(A)		57
(II/2)(V)		1000
(III/2)(V)		1000
(III/3)(V)		800
(II/2)(KV)		8
(III/2)(KV)		8
(III/3)(KV)		8
(mm ²)		0.5
(mm ²)		10
(mm ²)		0.5
(mm ²)		10
(mm ²) , , ,		0.5
(mm ²) , , ,		6
(mm ²) , , ,		0.5
(mm ²) , , ,		4
2 (mm ²)		4
2 (mm ²)		4
2 (mm ²) , , ,		0.5
2 (mm ²) , , ,		2.5
2 (mm ²) , , ,		0.5
2 (mm ²) , , ,		2.5
	M4	
Width)(mm) (Blade thickness x		1.0x5.5
Philips		PH2
(N.m)		1.8
		8~9

-UL

(UL/CUL Group B)(V)	600
---------------------	-----

(UL/CUL Group B)(A)		30
(UL/CUL Group C)(V)		600
(UL/CUL Group C)(A)		30
(UL/CUL Group D)(V)		600
(UL/CUL Group D)(A)		5
UL/CUL	AWG	18
UL/CUL	AWG	8
UL/CUL	AWG	18
UL/CUL	AWG	8

&

가	(YES or NO)	YES
		115
		-40

UL

(Group B)(AWG)	18~8
(Group B)(V)	600
(Group B)(A)	30
(Group C)(AWG)	18~8
(Group C)(V)	600
(Group C)(A)	30
(Group D)(AWG)	18~8
(Group D)(V)	600
(Group D)(A)	5

CUL

(Group B)(AWG)	18~8
(Group B)(V)	600
(Group B)(A)	30
(Group C)(AWG)	18~8
(Group C)(V)	600
(Group C)(A)	30
(Group D)(AWG)	18~8
(Group D)(V)	600

(Group D)(A)

5

