


# DK16N

DIN > :2025-11-05 :1.2





M5, 600V, 100A, Beige (default)

	Single Level Feed-through Terminal Block, Screw Connection
	Single Level Feed-through Terminal Block,
	Beige (default)
	Screw connection
	Rail mounting
(mm)	49.6
(mm)	12
(mm)	51.3
( )	1P
	Single level
	2

	PA
	I
UL 94	VO
	500M at DC 500V

## -IEC

(V)	1000
(A)	76
(III/3)(V)	1000
(III/3)(KV)	8
(mm <sup>2</sup> )	1.5
(mm²)	25
(mm <sup>2</sup> )	1.5
(mm <sup>2</sup> )	16
(mm <sup>2</sup> )	1.5
(mm²)	16
(mm ² )	1.5
(mm ² )	16
2 (mm²)	1.5
2 (mm²)	6
2 (mm²)	1.5
2 (mm²)	6
(mm <sup>2</sup> ) , ,	1.5
(mm²) , ,	6
2 , , , , (mm²)	1.5
2 , , , , (mm²)	10
	M5
(Blade thickness x Width)(mm)	1.0x5.5
Philips	PH2
(N.m)	2.0
(N.m)	3.4
	14~16
	TS-35、TS-35/15
	YES
	NO

### -UL

(UL/CUL (	Group B)(V)	600
(UL/CUL (	Group B)(A)	100
(UL/CUL (	Group C)(V)	600
(UL/CUL (	Group C)(A)	100
UL/CUL	AWG	14
UL/CUL	AWG	3
UL/CUL	AWG	14
UL/CUL	AWG	3

### &

	(YES or NO)	YES
가	(YES or NO)	YES
		120
		-40

### UL

(Group B)(AWG)	14~3
(Group B)(V)	600
(Group B)(A)	100
(Group C)(AWG)	14~3
(Group C)(V)	600
(Group C)(A)	100

### CUL

(Group B)(AWG)	14~3
(Group B)(V)	600
(Group B)(A)	100
(Group C)(AWG)	14~3
(Group C)(V)	600
(Group C)(A)	100

#### VDE

(mm²)	1.5~16



(V)	1000
(A)	76

