



0226-11XX

PCB > PCB -

:2025-05-01 :V1



Pitch : 5.00 mm, 300V, 10A

| | |
|------------------|--|
| | PCB Connector – Socket, Wave soldering |
| | PCB Connector – Socket |
| (mm) | 5.00 |
| | Black (default) |
| | With threaded flange |
| | Wave soldering |
| (mm) | $5.00 * (P - 1) + 14.9$ |
| (mm) | 11.35 |
| (mm) | 7.7 |
| (x) (mm) | 0.5x1.0 |
| PCB (mm) | 1.4 |
| () | 02P~16P |
| | Single level |
| | PA |
| | I |
| UL 94 | V0 |



| | |
|--|-----------------|
| | 500M at DC 500V |
| | COPPER ALLOY |
| | Tin PLATED |

-IEC

| | |
|-------------|------|
| (V) | 630 |
| (A) | 17.5 |
| (II/2)(V) | 630 |
| (III/2)(V) | 320 |
| (III/3)(V) | 320 |
| (II/2)(KV) | 4 |
| (III/2)(KV) | 4 |
| (III/3)(KV) | 4 |
| (N.m) | 0.3 |

-UL

| | |
|---------------------|-----|
| (UL/CUL Group B)(V) | 300 |
| (UL/CUL Group B)(A) | 10 |
| (UL/CUL Group D)(V) | 300 |
| (UL/CUL Group D)(A) | 10 |

&

| | |
|---------------|-----|
| 가 (YES or NO) | YES |
| | 120 |
| | -40 |

| | |
|--|--|
| | |
| | |
| | |

