



# 0226-26XX

PCB &gt; PCB -

:2026-07-04 :V1



Pitch : 5.00 mm, 300V, 10A

	PCB Connector – Socket, Wave soldering
	PCB Connector – Socket
(mm)	5.00
	Black (default)
	With mounting flange
	Wave soldering
(mm)	$5.00*(P-1) + 12.7$
(mm)	11.35
(mm)	6.5
(    x    ) (mm)	0.5x1.0
PCB (mm)	1.4
(    )	02P~16P
	Single level
	PA
	I
UL 94	V0



	500M at DC 500V
	COPPER ALLOY
	Tin PLATED

**-IEC**

(V)	630
(A)	17.5
(II/2)(V)	630
(III/2)(V)	320
(III/3)(V)	320
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4

**-UL**

(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	10
(UL/CUL Group D)(V)	300
(UL/CUL Group D)(A)	10

**&**

가 (YES or NO)	YES
	120
	-40

**UL**

(Group B)(V)	300
(Group B)(A)	10
(Group D)(V)	300
(Group D)(A)	10

**CUL**

(Group B)(V)	300
(Group B)(A)	10
(Group D)(V)	300

(Group D)(A)

10

