



# 0226-26XXL

PCB &gt; PCB -

:2026-02-09 :V1



Pitch : 5.00 mm, 300V, 10A

|                  |   |
|------------------|---|
|                  | PCB Connector – Socket, Reflow soldering  |
| (mm)             | PCB Connector – Socket  |
| (mm)             | 5.00  |
|                  | Black (default)   |
|                  | With mounting flange  |
|                  | Reflow Soldering (Temperature condition according to standard IPC/JEDEC J-STD-020E) |
| (mm)             | 5.00*(P-1)+12.7   |
| (mm)             | 11.35   |
| (mm)             | 6.5   |
| (    x    ) (mm) | 0.5x1.0   |
| PCB (mm)         | 1.4   |
| (    )           | 02P~16P   |
|                  | Single level  |

HIGH-TEMPERATURE PLASTICS

I



Delight Through Connections

UL 94

V0

500M at DC 500V

COPPER ALLOY

Tin PLATED

MSL

2

**-IEC**

|             |      |
|-------------|------|
| (V)         | 630  |
| (A)         | 17.5 |
| (II/2)(V)   | 630  |
| (III/2)(V)  | 320  |
| (III/3)(V)  | 320  |
| (II/2)(KV)  | 4    |
| (III/2)(KV) | 4    |
| (III/3)(KV) | 4    |

**-UL**

|                     |     |
|---------------------|-----|
| (UL/CUL Group B)(V) | 300 |
| (UL/CUL Group B)(A) | 10  |
| (UL/CUL Group D)(V) | 300 |
| (UL/CUL Group D)(A) | 10  |

**&**

|   |             |     |
|---|-------------|-----|
| 가 | (YES or NO) | YES |
|   |             | 120 |
|   |             | -40 |

**UL**

|              |     |
|--------------|-----|
| (Group B)(V) | 300 |
| (Group B)(A) | 10  |
| (Group D)(V) | 300 |
| (Group D)(A) | 10  |

**CUL**

|              |     |
|--------------|-----|
| (Group B)(V) | 300 |
|--------------|-----|

|              |     |
|--------------|-----|
| (Group B)(A) | 10  |
| (Group D)(V) | 300 |
| (Group D)(A) | 10  |

