


0226-27XXL

PCB > PCB - :2025-11-05 :V1





Pitch: 5.00 mm, 300V, 10A

	PCB Connector – Socket, Reflow soldering
	PCB Connector – Socket
(mm)	5.00
	Black (default)
	With mounting flange
	Reflow Soldering (Temperature condition according to standard IPC/JEDEC J-STD-020E)
(mm)	5.00*(P-1)+12.7
(mm)	6.5
(mm)	11.35
(x) (mm)	0.5x1.0
PCB (mm)	1.4
()	02P~16P
	Single level
	-

HIGH-TEMPERATURE PLASTICS
I

UL 94	V0
	500M at DC 500V
	COPPER ALLOY
	Tin PLATED
MSL	2
-IEC	
(V)	630
(A)	17.5
(II/2)(V)	630
(III/2)(V)	320
(III/3)(V)	320
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4
-UL	
(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	10
(UL/CUL Group D)(V)	300
(UL/CUL Group D)(A)	10
&	
가 (YES or NO)	YES
	120
	-40
UL	
(Group B)(V)	300
(Group B)(A)	10
(Group D)(V)	300
(Group D)(A)	10
CUL	
(Group B)(V)	300

(Group B)(A)	10
(Group D)(V)	300
(Group D)(A)	10

