


DK2.5N-TR

DIN > :2025-11-05 :1.2





M2.5, 600V, 20A, Beige (default)

	Single Level Feed-through Terminal Block, Screw Connection
	Single Level Feed-through Terminal Block,
	Beige (default)
	Screw connection
	Rail mounting
mm)	54.8
mm)	5.1
mm)	48.5
()	1P
	Single level
	4

	PA
	I
UL 94	VO
	500M at DC 500V

-IEC

(V)	1000
(A)	24
(III/3)(V)	1000
(II/2)(KV)	8
(III/2)(KV)	8
(III/3)(KV)	8
(mm²)	0.14
(mm²)	4
(mm²)	0.14
(mm²)	2.5
(mm ²)	0.25
(mm ²)	2.5
(mm ²)	0.25
(mm ²)	1.5
2 (mm²)	0.14
2 (mm²)	2.5
2 (mm²)	0.14
2 (mm²)	1.5
(mm ²)	0.25
(mm ²)	1.5
2 , , , , , (mm ²)	0.5
2 , , , , , (mm ²)	1
	M2.5
(Blade thickness x Width)(mm)	0.6x3.5
Philips	PH1
(N.m)	0.4
	9~11
	TS-35/ TS-35/15
	YES

		NO
-U	IL	
(UL/CUL Group B)(V)		600
(UL/CUL Group B)(A)		20
(UL/CUL Group C)(V)		600
(UL/CUL Group C)(A)		20
UL/CUL	AWG	22
UL/CUL	AWG	12
UL/CUL	AWG	22
UL/CUL	AWG	12
&		
(YES o	r NO)	YES
가 (YES o	r NO)	YES
		120
		-40
UL		
(Group B)	(AWG)	22~12
(Group B)(V)		600
(Group B)	(A)	20
(Group C)(AWG)		22~12
(Group C)(V)		600
(Group C)	(A)	20
CUL		
(Group B)(AWG)		22~12
(Group B)(V)		600
(Group B)(A)		20
(Group C)(AWG)		22~12
(Group C)(V)		600
(Group C)(A)		20

VDE

(mm ²)	0.14~2.5
(V)	1000
(A)	24

