


DK16N-PE

DIN > :2025-11-05 :1.2





M5, Green-Yellow (default)

	Grounding Terminal Block, Screw Connection
	Grounding Terminal Block
	Green-Yellow (default)
	Screw connection
	Rail mounting
(mm)	52
(mm)	12
(mm)	50.9
()	1P
	Single level
	2

	PA
	I
UL 94	VO
	500M at DC 500V

-IEC

(V)	1000
(III/3)(V)	1000
(III/3)(KV)	8
(mm ²)	1.5
(mm ²)	25
(mm ²)	1.5
(mm ²)	16
(mm ²)	1.5
(mm ²)	16
(mm ²)	1.5
(mm ²)	16
2 (mm²)	1.5
2 (mm²)	6
2 (mm²)	1.5
2 (mm²)	6
(mm²) , , ,	1.5
(mm²) , , ,	6
2 (mm²)	, 1.5
2 (mm²)	, 10
	M5
(Blade thickness x Width)(mm)	0.8x4.0
(N.m)	2.5
	12~14
	TS-35、TS-35/15
	YES
	YES
-UL	
(UL/CUL Group B)(V)	600

(UL/CUL	Group C)(V)	600
UL/CUL	AWG	14
UL/CUL	AWG	3
UL/CUL	AWG	14
UL/CUL	AWG	3

&

	(YES or NO)	YES
가	(YES or NO)	YES
		120
		-40

VDE

(mm ²)	1.5~16
, ,	

