



DP4N-PE

DIN

>

:2026-07-04

:1.1



600V, Green-Yellow (default)

| | |
|-------|------------------------------------------|
| | Grounding Terminal Block, Push-in Design |
| | Grounding Terminal Block |
| | Green-Yellow (default) |
| | Push-in Design |
| | Rail Mounting |
| (mm) | 57 |
| (mm) | 6.1 |
| (mm) | 35 |
| () | 1P |
| | Single level |
| | 2 |
| | PA |
| | I |
| UL 94 | V0 |
| | 500M at DC 500V |

-IEC

| | |
|----------------------------------------|----------------|
| (V) | 800 |
| (III/3)(V) | 800 |
| (III/3)(KV) | 8 |
| (mm ²) | 0.2 |
| (mm ²) | 6 |
| (mm ²) | 0.2 |
| (mm ²) | 4 |
| (mm ²) , , | 0.25 |
| (mm ²) , , | 4 |
| (mm ²) , , | 0.25 |
| (mm ²) , , | 4 |
| ² (mm ²) , , | 0.5 |
| ² (mm ²) , , | 1 |
| Width)(mm) (Blade thickness x | 0.8x4.0 |
| | 12~13 |
| | TS-35、TS-35/15 |
| | YES |
| | YES |

-UL

| | |
|---------------------|-----|
| (UL/CUL Group B)(V) | 600 |
| (UL/CUL Group C)(V) | 600 |
| UL/CUL AWG | 24 |
| UL/CUL AWG | 10 |
| UL/CUL AWG | 24 |
| UL/CUL AWG | 10 |

&

| | |
|---------------|-----|
| (YES or NO) | YES |
| 가 (YES or NO) | YES |

| | |
|--|-----|
| | 120 |
| | -40 |

UL

| | |
|----------------|-------|
| (Group B)(AWG) | 24~10 |
| (Group B)(V) | 600 |
| (Group C)(AWG) | 24~10 |
| (Group C)(V) | 600 |

CUL

| | |
|----------------|-------|
| (Group B)(AWG) | 24~10 |
| (Group B)(V) | 600 |
| (Group C)(AWG) | 24~10 |
| (Group C)(V) | 600 |

