



# DP4N-PE

DIN

>

:2026-05-14

:1.1



600V, Green-Yellow (default)

	Grounding Terminal Block, Push-in Design
	Grounding Terminal Block
	Green-Yellow (default)
	Push-in Design
	Rail Mounting
(mm)	57
(mm)	6.1
(mm)	35
( )	1P
	Single level
	2
	PA
	I
UL 94	V0
	500M at DC 500V

**-IEC**

(V)	800
(III/3)(V)	800
(III/3)(KV)	8
(mm <sup>2</sup> )	0.2
(mm <sup>2</sup> )	6
(mm <sup>2</sup> )	0.2
(mm <sup>2</sup> )	4
(mm <sup>2</sup> ) , ,	0.25
(mm <sup>2</sup> ) , ,	4
(mm <sup>2</sup> ) , ,	0.25
(mm <sup>2</sup> ) , ,	4
<sup>2</sup> (mm <sup>2</sup> ) , ,	0.5
<sup>2</sup> (mm <sup>2</sup> ) , ,	1
Width)(mm) (Blade thickness x	0.8x4.0
	12~13
	TS-35、TS-35/15
	YES
	YES

**-UL**

(UL/CUL Group B)(V)	600
(UL/CUL Group C)(V)	600
UL/CUL AWG	24
UL/CUL AWG	10
UL/CUL AWG	24
UL/CUL AWG	10

**&**

(YES or NO)	YES
가 (YES or NO)	YES

	120
	-40

UL

(Group B)(AWG)	24~10
(Group B)(V)	600
(Group C)(AWG)	24~10
(Group C)(V)	600

CUL

(Group B)(AWG)	24~10
(Group B)(V)	600
(Group C)(AWG)	24~10
(Group C)(V)	600

