


0183-11XX

PCB > PCB -

:2026-02-10



Pitch : 7.62mm, 300V, 25A

	PCB Connector – Socket, Wave soldering
	PCB Connector – Socket
(mm)	7.62
	Black (default)
	Without
	Wave soldering
(mm)	7.62*(P-1)+7.0
(mm)	12.65
(mm)	9.35
(x) (mm)	1x1
PCB (mm)	1.3
()	02P~12P
	Single level

UL 94	PBT
	IIIa
	V0

	1000M at DC 500V
	COPPER ALLOY
	Tin PLATED

-IEC

(V)	630
(A)	32
(II/2)(V)	630
(III/2)(V)	500
(III/3)(V)	400
(II/2)(KV)	6
(III/2)(KV)	6
(III/3)(KV)	6

-UL

(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	25
(UL/CUL Group C)(V)	300
(UL/CUL Group C)(A)	25
(UL/CUL Group D)(V)	600
(UL/CUL Group D)(A)	5

&

가	(YES or NO)	YES
		120
		-40

UL

(Group B)(V)	300
(Group B)(A)	25
(Group C)(V)	300
(Group C)(A)	25
(Group D)(V)	600
(Group D)(A)	5

CUL

(Group B)(V)	300
(Group B)(A)	25
(Group C)(V)	300
(Group C)(A)	25
(Group D)(V)	600
(Group D)(A)	5

