


## 2EHDVM-XXPLWR

PCB > :2025-11-05 :V1





Pitch: 5.08 mm, 300V, 15A

	PCB Connector - Socket, Reflow soldering
	PCB Connector - Socket
(mm)	5.08
	Black (default)
	With threaded flange
	Reflow Soldering (Temperature condition according to standard IPC/JEDEC J-STD-020E)
(mm)	5.08*(P-1)+15.14
(mm)	8.32
(mm)	12
( x ) (mm)	1.0x1.0
PCB (mm)	1.6
( )	02P~24P
	Single level

	HIGH-TEMPERAITAURE PLASTICS
UL 94	Vo
	500M at DC 500V
	COPPER ALLOY
	Tin PLATED
MSL	1
-IEC	
(V)	630
(A)	18
(II/2)(V)	630
(III/2)(V)	320
(III/3)(V)	250
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4
(N.m)	0.3
-UL	
(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	15
(UL/CUL Group D)(V)	300
(UL/CUL Group D)(A)	10
&	
가 (YES or NO)	NO
	120
	-40
IL	
(Group B)(V)	300
(Group B)(A)	15
(Group D)(V)	300
(Group D)(A)	10

## CUL

(Group B)(V)	300
(Group B)(A)	15
(Group D)(V)	300
(Group D)(A)	10

