

# 5EEHDHVC- XXPL

PCB > PCB -

:2026-07-06

Pitch : 5.00mm, 300V, 15A

	PCB Connector – Socket, Reflow Soldering
	PCB Connector – Socket
(mm)	5
	Black (default)
	Without
	Reflow Soldering
(mm)	$5.00 * (P/2-1) + 10.5$
(mm)	23.4
(mm)	26.16
(   x   ) (mm)	1x1
PCB (mm)	1.7
(   )	04P~48P
	Double level

	HIGH-TEMPERATURE PLASTICS
	a
UL 94	V0
	500M at DC 500V
	COPPER ALLOY
	Tin PLATED
MSL	1

### -IEC

(V)	630
(A)	18
(II/2)(V)	630
(III/2)(V)	320
(III/3)(V)	250
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4

### -UL

(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	15
(UL/CUL Group D)(V)	300
(UL/CUL Group D)(A)	15

### &

가 (YES or NO)	YES
	120
	-40

### UL

(Group B)(V)	300
(Group B)(A)	15
(Group D)(V)	300
(Group D)(A)	15



## CUL

(Group B)(V)	300
(Group B)(A)	15
(Group D)(V)	300
(Group D)(A)	15

