

3ESDSRH-XXP

PCB > PCB -

:2026-05-14

Pitch: 7.62 mm, 300V, 18A

	PCB Connector-Plug, Push-in Design
	PCB Connector – Plug
(mm)	7.62
	Green (default)
	Push in Design
	Without
(mm)	$7.62 * (P-1) + 5.3$
(mm)	15
(mm)	25.9
()	02P~12P
	Single level
	PA
	I



UL 94	V0
	500M at DC 500V
	HIGH PERFORMANCE COPPER ALLOY
	Tin PLATED

-IEC

(V)	1000
(A)	15
(II/2)(V)	1000
(III/2)(V)	630
(III/3)(V)	500
(II/2)(KV)	6
(III/2)(KV)	6
(III/3)(KV)	6
(mm ²)	0.2
(mm ²)	2.5
(mm ²)	0.2
(mm ²)	2.5
(mm ²) , ,	0.25
(mm ²) , ,	2.5
(mm ²) , ,	0.25
(mm ²) , ,	2.5
² (mm ²) , ,	0.5
² (mm ²) , ,	1
Width)(mm) (Blade thickness x	0.6x3.5
	10~11

-UL

(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	18
(UL/CUL Group D)(V)	300

(UL/CUL Group D)(A)		18
UL/CUL	AWG	26
UL/CUL	AWG	12
UL/CUL	AWG	26
UL/CUL	AWG	12

&

가	(YES or NO)	YES
		120
		-40

UL

(Group B)(AWG)		26~12
(Group B)(V)		300
(Group B)(A)		18
(Group D)(AWG)		26~12
(Group D)(V)		300
(Group D)(A)		18

CUL

(Group B)(AWG)		26~12
(Group B)(V)		300
(Group B)(A)		18
(Group D)(AWG)		26~12
(Group D)(V)		300
(Group D)(A)		18

