



3ESNVHM-XXP

PCB > PCB -

:2026-05-14



Pitch: 7.62mm, M3, 600V, 25A

	PCB Connector-Plug, Screw Connection
	PCB Connector – Plug
(mm)	7.62
	Green (default)
	Screw Connection
	With screw flange
(mm)	$7.62 \times (P-1) + 17.5$
(mm)	24.65
(mm)	19.75
()	02P~12P
	Single level
	PA
	I
UL 94	V0
	500M at DC 500V
	HIGH PERFORMANCE COPPER ALLOY



		Tin PLATED
-IEC		
(V)		1000
(A)		24
(II/2)(V)		1000
(III/2)(V)		1000
(III/3)(V)		1000
(II/2)(KV)		8
(III/2)(KV)		8
(III/3)(KV)		8
(mm ²)		0.2
(mm ²)		4
(mm ²)		0.2
(mm ²)		4
(mm ²)	,	0.25
(mm ²)	,	4
(mm ²)	,	0.25
(mm ²)	,	4
2	(mm ²)	0.2
2	(mm ²)	1.5
2	(mm ²)	0.2
2	(mm ²)	1.5
(mm ²) ²	,	0.25
(mm ²) ²	,	1.5
2	(mm ²)	0.5
2	(mm ²)	1.5
		M3
Width)(mm)	(Blade thickness x	0.8X4
	(N.m)	0.5

(N.m)	0.6
(N.m)	0.3
	7~8

-UL

(UL/CUL Group B)(V)	600
(UL/CUL Group B)(A)	25
(UL/CUL Group C)(V)	600
(UL/CUL Group C)(A)	25
(UL/CUL Group D)(V)	600
(UL/CUL Group D)(A)	5
UL/CUL AWG	28
UL/CUL AWG	10
UL/CUL AWG	28
UL/CUL AWG	10

&

가 (YES or NO)	YES
	120
	-40

UL

(Group B)(AWG)	28~10
(Group B)(V)	600
(Group B)(A)	25
(Group C)(AWG)	28~10
(Group C)(V)	600
(Group C)(A)	25
(Group D)(AWG)	28~10
(Group D)(V)	600
(Group D)(A)	5

CUL

(Group B)(AWG)	28~10
(Group B)(V)	600

(Group B) (A)	25
(Group C) (AWG)	28~10
(Group C) (V)	600
(Group C) (A)	25
(Group D) (AWG)	28~10
(Group D) (V)	600
(Group D) (A)	5

