



DKD10-P001

DIN > :2025-11-05





600V, 60A, Beige (default)

	Potential collective Terminal Block, Screw Connection /Push-in Design
	Potential collective Terminal Block
	Beige (default)
	Screw Connection /Push-in Design
	Rail Mounting
mm)	65.4
mm)	10.2
(mm)	35.8/ 37.3 (TS-35N) / 44.8 (TS-35/15N)
	Single level
	5

	PA
	I
UL 94	VO
	500M at DC 500V

-IEC

(V)	1000
(A)	57/24
(III/3)(V)	1000
(III/3)(KV)	8
(mm²)	0.5/0.14
(mm²)	10/4
(mm²)	0.5/0.14
(mm²)	10/2.5
(mm²)	0.5/0.25
(mm ²)	10/2.5
(mm²)	0.5/0.25
(mm²)	10/2.5
2 , , , , (mm ²)	0.5
2 , , , , (mm ²)	0.5
	M4
(Blade thickness x Width)(mm)	0.6x3.5/ PH1
(N.m)	1.2
(N.m)	1.5
	12~14 9~10
	TS-35N、TS-35/15N
	NO
	NO
-UL	
(UL/CUL Group B)(V)	600
(UL/CUL Group B)(A)	60/20
(UL/CUL Group C)(V)	600
(UL/CUL Group C)(A)	60/20
JL/CUL AWG	20/26
JL/CUL AWG	6/12
UL/CUL AWG	20/26



UL/CUL	AWG	6/12
&		
(YES	or NO)	YES
가 (YES	or NO)	YES
		120
		-40

