


DK2.5N-3L

DIN > :2025-11-05





600V, 20A, Beige (default)

| | Three level Feed-Through Terminal Block, Screw Connection |
|-----|---|
| | Three level Feed Through Terminal Block |
| | Beige (default) |
| | Screw Connection |
| | Rail Mounting |
| mm) | 90.7 |
| mm) | 5.1 |
| mm) | 76/77.3 (TS-35N) /84.8 (TS-35/15N) |
| | Three level |
| | 6 |
| | |

| | PA |
|-------|-----------------|
| | I |
| UL 94 | V0 |
| | 500M at DC 500V |

-IEC

| (V) | 1000 |
|-------------------------------|-------------------|
| (A) | 24 |
| (III/3)(V) | 1000 |
| (III/3)(KV) | 8 |
| (mm²) | 0.34 |
| (mm²) | 4 |
| (mm²) | 0.34 |
| (mm²) | 2.5 |
| (mm²) | 0.5 |
| (mm ²) | 2.5 |
| (mm ²) | 0.5 |
| (mm ²) | 2.5 |
| 2 (mm²) | 0.34 |
| 2 (mm²) | 1.5 |
| 2 (mm²) | 0.5 |
| 2 (mm²) | 1.5 |
| (mm ²) , , | 0.5 |
| (mm²) , , | 1.5 |
| 2 , , , , (mm ²) | 0.5 |
| 2 , , , , (mm ²) | 1.5 |
| | M2.5 |
| (Blade thickness x Width)(mm) | 0.6x3.5 |
| (N.m) | 0.4 |
| (N.m) | 0.4 |
| (N.m) | 0.5 |
| | 10 |
| | TS-35N、 TS-35/15N |
| | YES |
| | NO |

-UL

| (UL/CUL Group B)(V) | | 600 |
|---------------------|-------------|-----|
| (UL/CUL Group B)(A) | | 20 |
| (UL/CUL G | Group C)(V) | 600 |
| (UL/CUL G | Group C)(A) | 20 |
| (UL/CUL G | Group D)(V) | 600 |
| (UL/CUL G | Group D)(A) | 5 |
| UL/CUL | AWG | 22 |
| UL/CUL | AWG | 12 |
| UL/CUL | AWG | 22 |
| UL/CUL | AWG | 12 |
| | | |

&

| | (YES or NO) | YES |
|---|-------------|-----|
| 가 | (YES or NO) | YES |
| | | 120 |
| | | -40 |

UL

| 22~12 |
|-------|
| 600 |
| 20 |
| 22~12 |
| 600 |
| 20 |
| 22~12 |
| 600 |
| 20 |
| |

CUL

| (Group B)(AWG) | 22~12 |
|----------------|-------|
| (Group B)(V) | 600 |
| (Group B)(A) | 20 |
| (Group C)(AWG) | 22~12 |

| (Group C)(V) | 600 |
|----------------|-------|
| (Group C)(A) | 20 |
| (Group D)(AWG) | 22~12 |
| (Group D)(V) | 600 |
| (Group D)(A) | 20 |

