



DK2.5N-MLXX

DIN

>

:2026-07-05



300V, 10A, Beige (default)

	Fuse Terminal Block, Screw Connection
	Fuse Terminal Block
	Beige (default)
	Screw Connection
	Rail Mounting
(mm)	40.7
(mm)	5.1
(mm)	89.1
	Single level
	2
	PA
	I
UL 94	V0
	500M at DC 500V

-IEC



(V)	400
(A)	6.3 (the Current is determined by the fuse used)
(III/3)(V)	400
(III/3)(KV)	6.3
(mm ²)	0.34
(mm ²)	4
(mm ²)	0.34
(mm ²)	2.5
(mm ²) , ,	0.5
(mm ²) , ,	2.5
(mm ²) , ,	0.5
(mm ²) , ,	2.5
2 (mm ²)	0.34
2 (mm ²)	1.5
2 (mm ²)	0.5
2 (mm ²)	1.5
(mm ²) 2 , ,	0.5
(mm ²) 2 , ,	1.5
2 (mm ²) , ,	0.5
2 (mm ²) , ,	1.5
	M2.5
Width)(mm) (Blade thickness x	0.6x3.5
(N.m)	0.4
(N.m)	0.4
(N.m)	0.5
	9~11
	TS-35N、 TS-35/15N
	YES
	NO

-UL

(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		10
(UL/CUL Group C)(V)		300
(UL/CUL Group C)(A)		10
UL/CUL	AWG	22
UL/CUL	AWG	12
UL/CUL	AWG	22
UL/CUL	AWG	12

&

(YES or NO)		YES
가 (YES or NO)		YES
		120
		-40

