


DK4NS-M

DIN > :2025-11-05





300V, 10A, Beige (default)

	Fuse Terminal Block, Push-in Design
	Fuse Terminal Block
	Beige (default)
	Screw Connection
	Rail Mounting
mm)	57.8
mm)	6.7
(mm)	88.9/90.1(TS-35N)/97.6(TS-35/15N)
	Single level
	2

	PA
	I
UL 94	VO
	500M at DC 500V

-IEC


(V)	400
(A)	6.3 (the Current is determined by the fuse used)
(III/3)(V)	400
(III/3)(KV)	4
(mm ²)	0.34
(mm ²)	4
(mm ²)	0.34
(mm ²)	4
(mm ²)	0.34
(mm²)	4
(mm ²)	0.34
(mm ²)	4
2 (mm²)	0.34
2 (mm²)	2.5
2 (mm²)	0.34
2 (mm²)	2.5
(mm^2) , ,	0.34
(mm^2) , ,	1.5
2 , , , , , , , , , , , , , , , , , , ,	0.5
2 (mm²)	2.5
	M3
(Blade thickness x Width)(mm)	0.6x3.5
(N.m)	0.5
(N.m)	0.5
(N.m)	0.6
	9~11
	TS-35N、 TS-35/15N
	YES
	NO


-UL

(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		10
(UL/CUL Group C)(V)		300
(UL/CUL Group C)(A)		10
UL/CUL	AWG	22
UL/CUL	AWG	10
UL/CUL	AWG	22
UL/CUL	AWG	10

&

	(YES or NO)	YES
가	(YES or NO)	YES
		120
		-40





 ϵ

