


# 0189-214PL

PCB > PCB

:2026-07-05



Pitch :5.00mm, 300V, 20A

	PCB Terminal Blocks, Push-in Design
	PCB Terminal Blocks
(mm)	5
	Black (default)
	Push-in Design
	Without
	Wave Soldering
(mm)	20.6
(mm)	18.8
(mm)	22
( ) x ( ) (mm)	0.8x1
PCB (mm)	1.6
( )	04P
	Single level
	4
	PA



	I
UL 94	V0
	500M at DC 500V
	COPPER ALLOY
	Tin PLATED

**-IEC**

(V)	320
(A)	24
(II/2)(V)	320
(III/2)(V)	320
(III/3)(V)	200
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4
(mm <sup>2</sup> )	0.2
(mm <sup>2</sup> )	2.5
(mm <sup>2</sup> )	0.2
(mm <sup>2</sup> ) , ,	4
(mm <sup>2</sup> ) , ,	0.25
(mm <sup>2</sup> ) , ,	2.5
(mm <sup>2</sup> ) , ,	0.25
2 (mm <sup>2</sup> )	2.5
2 (mm <sup>2</sup> ) , ,	0.5
2 (mm <sup>2</sup> ) , ,	1
Width)(mm) (Blade thickness x	0.6x3.5
	10~11

**-UL**

(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	20



(UL/CUL Group D)(V)		300
(UL/CUL Group D)(A)		10
UL/CUL	AWG	24
UL/CUL	AWG	12
UL/CUL	AWG	24
UL/CUL	AWG	12

&

가	(YES or NO)	YES
		120
		-40

### UL

(Group B)(AWG)		24~12
(Group B)(V)		300
(Group B)(A)		20
(Group D)(AWG)		24~12
(Group D)(V)		300
(Group D)(A)		10

### CUL

(Group B)(AWG)		24~12
(Group B)(V)		300
(Group B)(A)		20
(Group D)(AWG)		24~12
(Group D)(V)		300
(Group D)(A)		10

--	--	--

