


PM4H-16P

NEMA

>

:2026-02-09



300V, 30A, Beige (default)

	Panel Mounting
	Panel Mounting
(mm)	10
	Refer to drawing
	Screw Connection
	With mounting flange
(mm)	$10 * (P-1) + 7.6$
(mm)	22.5
(mm)	18.7
()	02P~16P
	Single level
	2

UL 94	PA
	I
	V0
	500M at DC 500V

COPPER ALLOY

Tin PLATED

-IEC

(V)		630
(A)		32
(II/2)(V)		1000
(III/2)(V)		630
(III/3)(V)		630
(II/2)(KV)		6
(III/2)(KV)		6
(III/3)(KV)		6
(mm ²)		0.5
(mm ²)		4
(mm ²)		0.5
(mm ²)		4
(mm ²) , , ,		0.5
(mm ²) , , ,		4
(mm ²) , , ,		0.5
(mm ²) , , ,		4
2 (mm ²)		0.5
2 (mm ²)		2.5
2 (mm ²)		0.5
2 (mm ²)		2.5
2 (mm ²) , , ,		0.5
2 (mm ²) , , ,		2.5
2 (mm ²) , , ,		0.5
2 (mm ²) , , ,		2.5
		M3
Width)(mm)	(Blade thickness x	0.6x3.5

Philips	PH1
(N.m)	0.5
(N.m)	0.6
(N.m)	0.5
	7~8

-UL

(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	30
(UL/CUL Group C)(V)	300
(UL/CUL Group C)(A)	30
(UL/CUL Group D)(V)	600
(UL/CUL Group D)(A)	5
UL/CUL	AWG

&

(YES or NO)	YES
가 (YES or NO)	NO
	120
	-40

UL

(Group B)(AWG)	22~10
(Group B)(V)	300
(Group B)(A)	30
(Group C)(AWG)	22~10
(Group C)(V)	300
(Group C)(A)	30

CUL

(Group B)(AWG)	22~10
(Group B)(V)	300

(Group B)(A)	30
(Group C)(AWG)	22~10
(Group C)(V)	300
(Group C)(A)	30

