

0288-ADXX

PCB

> PCB

-

:2026-02-11



Pitch : 2.50 mm, 150V, 6A

Pluggable terminal block, Push-in Design

	Terminal Block
(mm)	2.5
	Black (default)
	Push-in Design
	With lock flange
(mm)	2.5*(P-1)+9.3
(mm)	5.2
(mm)	27.9
()	02P~12P
	Single level

UL 94	PA I V0 500M at DC 500V COPPER ALLOY Tin PLATED
-------	--

-IEC

(V)	320
(A)	6
(II/2)(V)	320
(III/2)(V)	160
(III/3)(V)	100
(II/2)(KV)	2.5
(III/2)(KV)	2.5
(III/3)(KV)	2.5
(mm ²)	0.14
(mm ²)	0.5
(mm ²)	0.25
(mm ²)	0.5
(mm ²) , , ,	0.25
(mm ²) , , ,	0.5

(mm ²) , ,	0.25
(mm ²) , ,	0.34
Width)(mm) (Blade thickness x	0.4X2.5
	7~8

-UL

(UL/CUL Group B)(V)	150
(UL/CUL Group B)(A)	6
UL/CUL AWG	26
UL/CUL AWG	18
UL/CUL AWG	26
UL/CUL AWG	18

&

가 (YES or NO)	YES
	120
	-40

