


4DSDAN-XX

> :2025-11-05





Pitch: 9.52mm, 300V, 15A

	Pluggable, Screw Connection
	Pluggable
(mm)	9.52
	Black (default)
	Screw connection
	With screw flange
(mm)	9.52*(P/2- 1)+16.79
(mm)	20
(mm)	29.85
()	08P~36P
	Bi-level
	8~36

	РВТ
	IIIa
UL 94	V0
	1000M at DC 500V

	COPPER ALLOY	
	Au PLATED	
-IEC		
(V)	320	
(A)	24	
(II/2)(V)	320	
(III/2)(V)	320	
(III/3)(V)	200	
(II/2)(KV)	4	
(III/2)(KV)	4	
(III/3)(KV)	4	
(mm ²)	0.75	
(mm ²)	2.5	
(mm ²)	0.75	
(mm ²)	2.5	
2 (mm²)	0.75	
2 (mm²)	1.5	
2 (mm²)	0.75	
2 (mm²)	1.5	
	M3.5	
(Blade thickness x Width)(mm)	1x5.5	
Philips	PH2	
(N.m)	0.8	
(N.m)	1	
(N.m)	0.5	
	8~9	
-UL		
(UL/CUL Group B)(V)	300	
(UL/CUL Group B)(A)	15	
(UL/CUL Group D)(V)	300	
(UL/CUL Group D)(A)	10	
UL/CUL AWG	18	



UL/CUL	AWG	14
UL/CUL	AWG	18
UL/CUL	AWG	14
&		
(YES or NO)		YES
		120
		-40
UL		
(Group B)(AWG)		18~14
(Group B)(V)		300
(Group B)(A)		15
(Group D)(AWG)		18~14
(Group D)(V)		300
(Group D)(A)		10
CUL		
(Group B)(AWG)		18~14
(Group B)(V)		300
(Group B)(A)		15
(Group D)(AWG)		18~14
(Group D)(V)		300
(Group D)(A)		10

