

DKB40N-XXPK

NEMA

>

:2026-03-30



Pitch : 11mm, M4, 600V, 40/60A

	Panel Mounting, Screw Connection
	Panel Mounting
(mm)	11
	Refer to drawing
	Screw Connection
(mm)	11.00*P+21
(mm)	38.5
(mm)	30
()	01P~16P
	Single level
	2~32
	PC
	a
UL 94	V2
	1000M at DC 500V
	COPPER ALLOY

		Tin PLATED
-IEC		
(V)		630
(A)		41
(III/3)(V)		630
(III/3)(KV)		8
(mm ²)		0.34
(mm ²)		6
(mm ²)		0.34
(mm ²)		6
2	(mm ²)	6
2	(mm ²)	6
		M4
Philips		PH2
(N.m)		1.2~1.5
(N.m)		1.2
(N.m)		1.5
(N.m)		0.8
		13~14 The stripping length depends on the specification provided by the cablelug manufacturer
		TS-35N、TS-35/15N
		YES
		NO
-UL		
(UL/CUL Group B)(V)		600
(UL/CUL Group B)(A)		40
(UL/CUL Group C)(V)		600
(UL/CUL Group C)(A)		40
(UL/CUL Group D)(V)		600
(UL/CUL Group D)(A)		40
UL/CUL	AWG	22
UL/CUL	AWG	8
UL/CUL	AWG	22



UL/CUL	AWG	8
&		
	(YES or NO)	YES
가	(YES or NO)	NO
		125
		-40

UL

	(Group B)(AWG)	22-8/(2)22-(2)10
	(Group B)(V)	600
	(Group B)(A)	40/60
	(Group C)(AWG)	22-8/(2)22-(2)10
	(Group C)(V)	600
	(Group C)(A)	40/60
	(Group D)(AWG)	22-8/(2)22-(2)10
	(Group D)(V)	600
	(Group D)(A)	5

CUL

	(Group B)(AWG)	22-8/(2)22-(2)10
	(Group B)(V)	600
	(Group B)(A)	40/60
	(Group C)(AWG)	22-8/(2)22-(2)10
	(Group C)(V)	600
	(Group C)(A)	40/60
	(Group D)(AWG)	22-8/(2)22-(2)10
	(Group D)(V)	600
	(Group D)(A)	5

--	--	--

