


DT-31-B01W-XX

> :2025-11-05 :1.1





Pitch: 8.25mm, #6-32, 300V, 20A

	Barrier terminal blocks, Screw connection
	Single Row
(mm)	8.25
	Black (default)
	Screw connection
	Without
	Wave Soldering
(mm)	8.25*(P-1)+9.56
(mm)	13.00
(mm)	13.00
(x) (mm)	0.8x1.0
PCB (mm)	1.3~1.4
()	02P~30P
	Single Row

PA66
I

UL 94	VO
	500M at DC 500V
	COPPER ALLOY
	Tin PLATED
-IEC	
(V)	320
(A)	24
(II/2)(V)	630
(III/2)(V)	320
(III/3)(V)	250
(II/2)(KV)	4
(III/2)(KV)	4
(III/3)(KV)	4
(mm²)	0.2
(mm²)	2.5
(mm²)	0.2
(mm ²)	2.5
2 (mm²)	1.5
2 (mm²)	1.5
	#6-32
(Blade thickness x Width)(mm)	0.8x4.0
Philips	PH2
(N.m)	1
(N.m)	0.8
(N.m)	1
	7~8
-UL	
(UL/CUL Group B)(V)	300
(UL/CUL Group B)(A)	20
(UL/CUL Group C)(V)	150
(UL/CUL Group C)(A)	20
(UL/CUL Group D)(V)	300

(UL/CUL Gro	oup D)(A)	10
UL/CUL	AWG	22
UL/CUL	AWG	12
UL/CUL	AWG	22
UL/CUL	AWG	12
&		
	10)	VEC
(YES or NO)		YES
		120
		-40
UL		
(Group B)(A	WG)	22~12
(Group B)(V	′)	300
(Group B)(A	A)	20
(Group C)(A	WG)	22~12
(Group C)(V)	150
(Group C)(A)		20
(Group D)(AWG)		22~12
(Group D)(V)		300
(Group D)(A)		10
CUL		
(Group B)(AWG)		22~12
(Group B)(V)		300
(Group B)(A)		20
(Group C)(AWG)		22~12
(Group C)(V)		150
(Group C)(A)		20
(Group D)(AWG)		22~12
(Group D)(V)		300
(Group D)(A)		10
CSA		
(AWG)		22~16



(V)	300
(A)	15

