



# DT-4C-B14W-XX

&gt;

:2025-12-26

:1.1



Pitch: 9.50mm , M3.5, 300V, 20A

	Barrier terminal blocks , Screw connection
	Single Row
(mm)	9.50
	Black(default)
	Screw connection
	Without
(    x    ) (mm)	0.8X1.5
PCB (mm)	2.0~2.1
	Single Row

UL 94	PBT IIIa V0
	Copper Alloy Tinned

-IEC



Delight Through Connections

(V)		500
(A)		24
(II/2)(V)		630
(III/2)(V)		500
(III/3)(V)		400
(II/2)(KV)		6
(III/2)(KV)		6
(III/3)(KV)		6
(mm <sup>2</sup> )		0.2
(mm <sup>2</sup> )		2.5
(mm <sup>2</sup> )		0.2
(mm <sup>2</sup> )		2.5
2	(mm <sup>2</sup> )	1.5
2	(mm <sup>2</sup> )	1.5
		M3.5
Width)(mm)	(Blade thickness x	0.8x4.0
Philips		PH2
(N.m)		1.2
(N.m)		0.8
(N.m)		1.2
		8~9

### -UL

(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		20
(UL/CUL Group D)(V)		300
(UL/CUL Group D)(A)		10
UL/CUL	AWG	22
UL/CUL	AWG	12
UL/CUL	AWG	22
UL/CUL	AWG	12

&amp;

(YES or NO)	YES
-------------	-----

130

-40

**UL**



(Group B)(AWG)	22~12
(Group B)(V)	300
(Group B)(A)	20
(Group D)(AWG)	22~12
(Group D)(V)	300
(Group D)(A)	10

**CUL**

(Group B)(AWG)	22~12
(Group B)(V)	300
(Group B)(A)	20
(Group D)(AWG)	22~12
(Group D)(V)	300
(Group D)(A)	10

**VDE**

(mm <sup>2</sup> )	0.2~2.5
(V)	500
(A)	24





Delight Through Connections

