


0032-10XX

>

:2026-05-14 :1.2



Pitch : 7.62mm , M3 , 300V , 10A

	Barrier terminal blocks , Screw connection
	Bi-level terminal blocks
(mm)	7.62
	Black(default)
	Screw connection
	Without
(x) (mm)	0.8x1.0
PCB (mm)	1.6~1.7
	Bi-level
	PBT
	IIIa
UL 94	V0
	Copper Alloy
	Tinned

-IEC

(A)		17.5
(II/2)(V)		200
(III/2)(V)		160
(III/3)(V)		100
(II/2)(KV)		2.5
(III/2)(KV)		2.5
(III/3)(KV)		2.5
(mm ²)		0.5
(mm ²)		1.5
(mm ²)		0.5
(mm ²)		1.5
2	(mm ²)	1
2	(mm ²)	1
		M3
Width)(mm)	(Blade thickness x	0.8x4.0
Philips		PH2
	(N.m)	0.8
	(N.m)	0.5
	(N.m)	0.8
		7~8

-UL

(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		10
(UL/CUL Group D)(V)		300
(UL/CUL Group D)(A)		10
UL/CUL	AWG	24
UL/CUL	AWG	16
UL/CUL	AWG	24
UL/CUL	AWG	16

&

(YES or NO)		YES
		130

-40

UL

(Group B) (AWG)	24~16
(Group B) (V)	300
(Group B) (A)	10
(Group D) (AWG)	24~16
(Group D) (V)	300
(Group D) (A)	10

VDE

(mm ²)	0.5~1.5
(A)	17.5

