



DT-35C-A01W-XX

>

:2026-07-05 :1.1



Pitch: 8.25mm , M3, 300V, 20A

	Barrier terminal blocks, Screw connection
	Single Row
(mm)	8.25
	Black (default)
	Screw connection
	With mounting flange
(x) (mm)	0.8X1.2
PCB (mm)	1.8~2.0
	Single Row
	PA66
	I
UL 94	V0
	Copper Alloy
	Tinned

-IEC

(V)		630
(A)		24
(II/2)(V)		630
(III/2)(V)		630
(III/3)(V)		320
(II/2)(KV)		6
(III/2)(KV)		6
(III/3)(KV)		6
(mm ²)		0.2
(mm ²)		2.5
(mm ²)		0.2
(mm ²)		2.5
2	(mm ²)	1.5
2	(mm ²)	1.5
		M3
Width)(mm)	(Blade thickness x	0.8x4.0
Philips		PH2
(N.m)		1.4
(N.m)		0.5
(N.m)		1.4
		7~8

-UL

(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		20
(UL/CUL Group C)(V)		150
(UL/CUL Group C)(A)		20
(UL/CUL Group D)(V)		300
(UL/CUL Group D)(A)		10
UL/CUL	AWG	22
UL/CUL	AWG	12
UL/CUL	AWG	22
UL/CUL	AWG	12



&

(YES or NO)	YES
	120
	-40

UL

(Group B) (AWG)	22~12
(Group B) (V)	300
(Group B) (A)	20
(Group C) (AWG)	22~12
(Group C) (V)	150
(Group C) (A)	20
(Group D) (AWG)	22~12
(Group D) (V)	300
(Group D) (A)	10

CUL

(Group B) (AWG)	22~12
(Group B) (V)	300
(Group B) (A)	20
(Group C) (AWG)	22~12
(Group C) (V)	150
(Group C) (A)	20
(Group D) (AWG)	22~12
(Group D) (V)	300
(Group D) (A)	10

VDE

(mm ²)	0.2~2.5
(A)	24

--	--

