



4DC-B34W-XX

>

:2026-07-05 :1.2



Pitch : 9.52mm , M3.5 , 300V , 20A

	Barrier terminal blocks , Screw connection
	Bi-level terminal blocks
(mm)	9.52
	Black(default)
	Screw connection
	Without
(x) (mm)	0.8x1.0
PCB (mm)	1.6
	Bi-level
	PBT
	IIIa
UL 94	V0
	Copper Alloy
	Tinned

-IEC



(A)		24
(II/2)(V)		320
(III/2)(V)		320
(III/3)(V)		250
(II/2)(KV)		4
(III/2)(KV)		4
(III/3)(KV)		4
(mm ²)		0.75
(mm ²)		2.5
(mm ²)		0.75
(mm ²)		2.5
2	(mm ²)	1.5
2	(mm ²)	1.5
		M3.5
Width)(mm)	(Blade thickness x	0.8x4.0
Philips		PH2
	(N.m)	1.4
	(N.m)	0.8
	(N.m)	1.4
		8

-UL

(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		20
UL/CUL	AWG	18
UL/CUL	AWG	12
UL/CUL	AWG	14
UL/CUL	AWG	12

&

(YES or NO)		YES
		130
		-40

UL

(Group B) (AWG)	18~12
(Group B) (V)	300
(Group B) (A)	20

VDE

(mm ²)	0.75~2.5
(A)	24

