


4DSDCC-01-XX

> :2025-11-05 :1.1





Pitch: 9.50 mm, M3.5, 300V, 15A

	Barrier terminal blocks , Screw connection
	Pluggable terminal blocks
(mm)	9.50
	Black(default)
	Screw connection
	With screw flange
(x) (mm)	0.8x1.1
CB (mm)	1.6~1.7
	Double level

	PBT
	IIIa
UL 94	VO
	Copper Alloy
	Gold plated

-IEC

(V)		250
(A)		24
(II/2)(V)		250
(III/2)(V)		250
(III/3)(V)		160
(II/2)(KV)		4
(III/2)(KV)		4
(III/3)(KV)		4
(mm ²)		0.75
(mm ²)		1.5
(mm ²)		0.75
(mm ²)		1.5
2	(mm ²)	1.5
2	(mm ²)	1.5
		M3.5
(Bla	de thickness x	0.8x4.0
Philips		PH2
(N.m)		1.4
(N.m)		0.8
(N.m)		1.4
		8~9
-UL		
(UL/CUL Group B)(V))	300
(UL/CUL Group B)(A		15
UL/CUL A	AWG	18
UL/CUL A	\WG	14
UL/CUL A	AWG	18
UL/CUL A	\WG	14
&		
(YES or NO)		YES
· · · · ·		130
		-40

UL

(Group B)(AWG)	18~14
(Group B)(V)	300
(Group B)(A)	15

CUL

(Group B)(AWG)	18~14
(Group B)(V)	300
(Group B)(A)	15

VDE

(mm ²)	0.75~1.5
(V)	250
(A)	24

