


4DSDAC-XX

> :2025-11-05 :1.1





Pitch: 9.50 mm, M3.5, 300V, 15A

	Barrier terminal blocks, Screw connection
	Pluggable terminal blocks
(mm)	9.50
	Black(default)
	Screw connection
	With screw flange
	Double level

	PBT
	IIIa
UL 94	VO
	Copper Alloy
	Gold plated

-IEC

(V)	250
(A)	24

(II/2)(V)		250
(III/2)(V)		250
(III/3)(V)		160
(11/2)	(KV)	4
(111/2)(KV)	4
(111/3)(KV)	4
(n	nm²)	0.75
(n	nm²)	2.5
(mm ²)		0.75
(n	nm²)	2.5
	2 (mm²)	1.5
2 (mm²)		1.5
		M3.5
Width)(mm)	(Blade thickness x	0.8x4.0
Philips		PH2
(N.r	m)	1.4
	(N.m)	0.8
	(N.m)	1.4
		8~9
- (JL	
(UL/CUL Group B)(V)		300
	Group B)(A)	15
UL/CUL	AWG	18
UL/CUL	AWG	14
UL/CUL	AWG	18
UL/CUL	AWG	14
&		
(YES or NO)		YES
		130
		-40

UL

(Group B)(AWG)	18~14
(Group B)(V)	300
(Group B)(A)	15

CUL

(Group B)(AWG)	18~14
(Group B)(V)	300
(Group B)(A)	15

VDE

(mm ²)	0.75~2.5
(V)	250
(A)	24

