



0168-13XX

>

:2026-02-09

:1.1



Pitch: 8.5mm , M3.5, 300V, 20A

| | |
|-------|--|
| | Barrier terminal blocks , Screw connection |
| | Panel Feed Through Terminal Blocks |
| (mm) | 8.5 |
| | Black(default) |
| | Screw connection |
| | With mounting flange |
| | Single level |
| UL 94 | PBT IIIa V0 |
| | Copper Alloy |
| | Tinned |

-IEC

| | |
|-----------|-----|
| (A) | 32 |
| (II/2)(V) | 630 |



Delight Through Connections

| | | |
|--------------------|--------------------|---------|
| (III/2)(V) | | 600 |
| (III/3)(V) | | 400 |
| (II/2)(KV) | | 6 |
| (III/2)(KV) | | 6 |
| (III/3)(KV) | | 6 |
| (mm ²) | | 0.34 |
| (mm ²) | | 4 |
| (mm ²) | | 0.34 |
| (mm ²) | | 4 |
| 2 | (mm ²) | 2.5 |
| 2 | (mm ²) | 4 |
| | | M3.5 |
| Width)(mm) | (Blade thickness x | 0.8x4.0 |
| Philips | | PH2 |
| (N.m) | | 1 |
| (N.m) | | 0.5 |
| (N.m) | | 1 |
| | | 8~9 |

-UL

| | | |
|---------------------|-----|-----|
| (UL/CUL Group B)(V) | | 300 |
| (UL/CUL Group B)(A) | | 20 |
| UL/CUL | AWG | 22 |
| UL/CUL | AWG | 12 |
| UL/CUL | AWG | 22 |
| UL/CUL | AWG | 12 |

&

| | |
|-------------|-----|
| (YES or NO) | YES |
| | 130 |
| | -40 |

UL

| | |
|----------------|-------|
| (Group B)(AWG) | 22~12 |
|----------------|-------|

| | |
|--------------|-----|
| (Group B)(V) | 300 |
| (Group B)(A) | 20 |

CUL

| | |
|----------------|-------|
| (Group B)(AWG) | 22~12 |
| (Group B)(V) | 300 |
| (Group B)(A) | 20 |

