



DT-29-A03W-XX

>

:2026-05-14 :1.1



Pitch: 6.35mm, M2.6, 300V, 15A

	Barrier terminal blocks, Screw connection
	Single Row
(mm)	6.35
	Black (default)
	Screw connection
	With mounting flange
(mm)	$6.35 * (P-1) + 19.1$
(mm)	14.00
(mm)	12.60
(x) (mm)	0.8x2.5
()	02P~33P
	Single Row
	PA66
	I
UL 94	V0
	500M at DC 500V

		COPPER ALLOY
		Tin PLATED
-IEC		
(V)		320
(A)		17.5
(II/2)(V)		630
(III/2)(V)		320
(III/3)(V)		200
(II/2)(KV)		4
(III/2)(KV)		4
(III/3)(KV)		4
(mm ²)		0.34
(mm ²)		1.5
(mm ²)		0.34
(mm ²)		1.5
2	(mm ²)	1
2	(mm ²)	1
		M2.6
Width)(mm)	(Blade thickness x	0.6x0.35
Philips		PH1
(N.m)		0.5
(N.m)		0.4
(N.m)		0.5
		6~7
-UL		
(UL/CUL Group B)(V)		300
(UL/CUL Group B)(A)		15
(UL/CUL Group D)(V)		300
(UL/CUL Group D)(A)		10
UL/CUL	AWG	22
UL/CUL	AWG	16
UL/CUL	AWG	22



UL/CUL	AWG	16
&		
(YES or NO)		YES
		120
		-40

UL

(Group B)(AWG)	22~16
(Group B)(V)	300
(Group B)(A)	15
(Group D)(AWG)	22~16
(Group D)(V)	300
(Group D)(A)	10

CUL

(Group B)(AWG)	22~16
(Group B)(V)	300
(Group B)(A)	15
(Group D)(AWG)	22~16
(Group D)(V)	300
(Group D)(A)	10

CSA

(AWG)	22~16
(V)	300
(A)	10

--	--

