


## PPAC-95M

PCB > :2025-11-05 :1.2





M8, 600V, 230A

	Panel Feed-Through, Screw Connection
	Panel Feed-Through
	Grey (default)
	Screw connection
	Without
(mm)	25
(mm)	50+45
(mm)	100
( )	1P

	PA
	I
UL 94	Vo
	500M at DC 500V
	COPPER ALLOY
	Tin PLATED

## -IEC

(V)	630V (5.0 ~ 6.0mm mounting plate), 800V (2.5 ~ 5.0mm mounting plate), 1000V (1.0 ~ 2.5mm mounting plate)
(A)	232
(III/3)(V)	630V (5.0 ~ 6.0mm mounting plate), 800V (2.5 ~ 5.0mm mounting plate), 1000V (1.0 ~ 2.5mm mounting plate)
(III/3)(KV)	8
(mm <sup>2</sup> )	25
(mm <sup>2</sup> )	95
(mm <sup>2</sup> )	25
(mm <sup>2</sup> )	95
(mm ² )	25
(mm <sup>2</sup> )	95
(mm <sup>2</sup> )	25
(mm²)	95
2 (mm²)	25
2 (mm²)	35
2 (mm²)	25
2 (mm <sup>2</sup> )	35
(mm²) , , ,	16
(mm²) , , ,	35
	M8
Philips	#6
(N.m)	15
	26~27
-UL	
(UL/CUL Group B)(V)	600
(UL/CUL Group B)(A)	230
(UL/CUL Group C)(V)	600
(UL/CUL Group C)(A)	230

UL/CUL	AWG	4
UL/CUL	AWG	4/0
UL/CUL	AWG	4
UL/CUL	AWG	4/0
&		
α		
(YES or NO)		YES
가 (YES or NO)		YES
		120
		-40
UL		
(Group B)(AWG)		4~4/0
(Group B)(V)		600
(Group B)(A)		230
(Group C)(AWG)		4~4/0
(Group C)(V)		600
(Group C)(A)		230
CUL		
(Group B)(AWG)		4~4/0
(Group B)(V)		600
(Group B)(A)		230
(Group C)(AWG)		4~4/0
(Group C)(V)		600
(Group C)(A)		230
( ) (		

