


ECH350RT-XXPLWR

PCB Terminal Blocks > In tape-on-reel packing

Date:2025-11-04Version:V1





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

Pitch: 3.50 mm, 300V, 8A

General information

Short description	PCB Connector – Socket, Reflow soldering
Category	PCB Connector – Socket
Pitch (mm)	3.5
Color	Black (default)
Type of locking	With lock flange
Soldering method	Reflow Soldering (Temperature condition according to standard IPC/JEDEC J-STD-020E)
Length (mm)	3.50*(P-1)+6.5
Width (mm)	9.2
Height (mm)	7.2
Pin demensions (Thickness x Width)(mm)	0.8x0.8
PCB hole diameter (mm)	1.4
Number of positions	02P~24P
Level	Single level




Material information

Insulation material	HIGH-TEMPERATURE PLASTICS
Insulation material group	IIIa
Flame retardant rating , compliant with UL94	V0
Insulation resistance	□500MΩ at DC 500V
Conductor material	COPPER ALLOY
Plating of conductor surface	Tin PLATED
MSL	1
Connection data-IEC	
Rated voltage (V)	320
Rated current (A)	14
Rated voltage (II/2)(V)	320
Rated voltage (III/2) (V)	160
Rated voltage (III/3)(V)	160
Rated impulse voltage (II/2)(KV)	2.5
Rated impulse voltage (III/2)(KV)	2.5
Rated impulse voltage (III/3)(KV)	2.5
Connection data-UL	
Rated voltage (UL/CUL Group B)(V)	300
Rated current (UL/CUL Group B)(A)	8
B . I I . (III (CI II C B) A B	300
Rated voltage (UL/CUL Group D)(V)	
Rated voltage (UL/CUL Group D)(V) Rated current (UL/CUL Group D)(A)	8
Rated current (UL/CUL Group D)(A)	
Rated current (UL/CUL Group D)(A)	
Rated current (UL/CUL Group D)(A) Environment & Safety	8
Rated current (UL/CUL Group D)(A) Environment & Safety Finger protection (YES or NO)	NO NO
Rated current (UL/CUL Group D)(A) Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C)	NO 120
Rated current (UL/CUL Group D)(A) Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C)	NO 120
Rated current (UL/CUL Group D)(A) Environment & Safety Finger protection (YES or NO) Operating temperature. max (°C) Operating temperature. min (°C) UL Recognized	NO 120 -40



Rated current (Group D)(A)	8
CUL Recognized	
Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	8
Rated voltage (Group D)(V)	300
Rated current (Group D)(A)	8

Drawings



Approvals





