


DPP1.5N-L2PE

DIN Rail Terminal Blocks > Push-in Design

Date:2025-11-03





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

300V, 15A, Beige (default)

General information

Short description	Grounding Terminal Blocks
Category	Grounding Terminal Block
Color	Beige (default)
Connection method	Push-in Design
Type of locking	Rail Mounting
Length (mm)	69
Width (mm)	3.5
Height (mm)	41.2
Number of positions	<u>≥</u> 1P
Level	Double level
Connection points	4


Material information


Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	VO

Insulation resistance	□500MΩ at DC 500V	
Connection data-IEC		
Rated voltage (V)	500	
Rated current (A)	17.5	
Rated voltage (III/3)(V)	500	
Rated impulse voltage (III/3)(KV)	6	
Conductor cross section solid. min (mm²)	0.2	
Conductor cross section solid.max (mm²)	1.5	
Conductor cross section stranded. min (mm²)	0.2	
Conductor cross section stranded. max (mm²)	1.5	
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.25	
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	1.5	
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.25	
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	0.75	
Slotted screwdriver size (Blade thickness x Width)(mm)	0.4x2.5	
Stripping Length (mm)	8~9	
Mounting rail	TS-35	
End cover plate required	YES	
Grounding connections	YES	
Connection data-UL		
Rated voltage (UL/CUL Group B)(V)	300	
Rated current (UL/CUL Group B)(A)	15	
Rated voltage (UL/CUL Group C)(V)	300	
Rated current (UL/CUL Group C)(A)	15	
Min. solid wire connection (AWG) acc. to UL/CUL	26	
Max. solid wire connection AWG acc. to UL/CUL	14	
Min. stranded wire connection AWG acc. to UL/CUL	26	
Max. stranded wire connection AWG acc. to UL/CUL	14	
Environment & Safety		
Back of the hand protection (YES or NO)	YES	

Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40

Drawings





Approvals





