



# DKD35-P002

DIN Rail Terminal Blocks > Push-in Design

Date:2025-11-04





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

### **Product Description**

600V, 102A, Beige (default)

#### General information

Short description	Potential collective Terminal Block, Screw Connection / Push-in Design
Category	Potential collective Terminal Block
Color	Beige (default)
Connection method	Screw Connection / Push-in Design
Length (mm)	108
Width (mm)	16
Height (mm)	47
Level	Single level
Connection points	13

#### Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	VO
Insulation resistance	□500MΩ at DC 500V



### Connection data-IEC

Rated voltage (V)	1000
Rated current (A)	Line Side: 105 / Load Side: 24
Rated voltage (III/3)(V)	1000
Rated impulse voltage (III/3)(KV)	Line Side: 8 / Load Side: 8
Conductor cross section solid. min (mm²)	Line Side: 1.5 / Load Side: 0.14
Conductor cross section solid.max (mm²)	Line Side: 50 / Load Side: 4
Conductor cross section stranded. min (mm²)	Line Side: 1.5 / Load Side: 0.14
Conductor cross section stranded. max (mm²)	Line Side: 35 / Load Side: 2.5
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	Line Side: 1.5 / Load Side: 0.25
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	Line Side: 35 / Load Side: 2.5
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	Line Side: 1.5 / Load Side: 0.25
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	Line Side: 35 / Load Side: 2.5
2 conductors with same cross section, solid, min (mm²)	Line Side: 1.5
2 conductors with same cross section, solid, max (mm²)	Line Side: 16
2 conductors with same cross section, stranded, min (mm²)	Line Side: 1.5
2 conductors with same cross section, stranded, max (mm²)	Line Side: 10
2 conductors with same cross section flexible, with min ferrule without plastic sleeve (mm²)	Line Side: 1.5
2 conductors with same cross section flexible, with max ferrule without plastic sleeve (mm²)	Line Side: 10
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	Line Side: 1.5 / Load Side: 0.5
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)	Line Side: 10 / Load Side: 0.5
Mounting rail	TS-35

## Connection data-UL

Rated voltage (UL/CUL Group B)(V)	600
Rated current (UL/CUL Group B)(A)	102 ( Line ) 20 ( Load )
Rated voltage (UL/CUL Group C)(V)	600
Rated current (UL/CUL Group C)(A)	102 ( Line ) 20 ( Load )
Rated voltage (UL/CUL Group D)(V)	600



Rated current (UL/CUL Group D)(A)	5
Min. solid wire connection (AWG) acc. to UL/CUL	Line Side: 12 / Load Side: 26
Max. solid wire connection AWG acc. to UL/CUL	Line Side: 1/0 / Load Side: 12
Min. stranded wire connection AWG acc. to UL/CUL	Line Side: 12 / Load Side: 26
Max. stranded wire connection AWG acc. to UL/CUL	Line Side: 1/0 / Load Side: 12


# **UL** Recognized


Wire Range (Group B)(AWG)	Line Side: 12~1/0 / Load Side: 26~12
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	Line Side: 102 / Load Side: 20
Wire Range (Group C)(AWG)	Line Side: 12~1/0 / Load Side: 26~12
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	Line Side: 102 / Load Side: 20
Wire Range (Group D)(AWG)	Line Side: 12~1/0 / Load Side: 26~12
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	Line Side: 102 / Load Side: 20

# **CUL** Recognized

Wire Range (Group B)(AWG)	Line Side: 12~1/0 / Load Side: 26~12
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	Line Side: 102 / Load Side: 20
Wire Range (Group C)(AWG)	Line Side: 12~1/0 / Load Side: 26~12
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	Line Side: 102 / Load Side: 20
Wire Ranget (Group D)(AWG)	Line Side: 12~1/0 / Load Side: 26~12
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	Line Side: 102 / Load Side: 20

# Drawings





# **Approvals**





